




Nailer-T

Wood Nailer Alternative



PRODUCT DATA SHEET

DESCRIPTION

Replacing wood nailers at the building perimeter with Nailer-T increases the structural integrity of the roof perimeter, significantly reduces risk of failure, and helps protect the entire roof system from costly damages and blow off. Nailer-T comes in varying sizes for low slope applications. Using Nailer-T, insulation can be continuous directly to the roofs edge, improving thermal performance. It is industry tested and easy to install with pre-punched fastening holes to ensure proper installation, every time.

MATERIALS

- Heavy Gauge Extruded Aluminum

SUBSTRATES

- Existing Wood Nailer
- Masonry
- Metal Deck

STANDARD SIZES

- 1.5" x 2.5" (Use with existing wood nailer)
- 1.5" x 5.5" (Use with masonry or metal)
- 3" x 2.5" (Use with existing wood nailer)
- 3" x 5.5" (Use with masonry or metal)
- 5.2" x 4" (Use with existing wood nailer, masonry or metal)
- 5.2" x 5.5" (Use with existing wood nailer, masonry or metal)

EFFICIENT DESIGN

- Provided in 12'-0" lengths with pre-punched holes to install up to 60% faster than wood nailers.
- Slotted fastening holes allow for proper thermal movement of the materials and ensure correct fastener placement and spacing.
- Extend insulation to the roof edge for increased thermal performance.
- It won't crack, warp, split or rot; it is not a food source for insects, non-combustible and won't absorb moisture.

INSTALLATION ADVANTAGE

- 1.5" sizes replace 1 wood nailer and allows 1.5" of Polyiso and ½" cover board or up to 2" of Polyiso
- 3" sizes replace 2 wood nailers and allows 3" of Polyiso and ½" cover board or up to 3.5" of Polyiso
- 5.2" sizes replace 3 wood nailers and allows 5.2" of Polyiso and ½" cover board or up to 5.7" of Polyiso

ADDED THERMAL BENEFITS

- 1.5" up to an added R-11.4 to the edge
- 3" sizes up to an added R-20.5 to the edge
- 5.2" sizes up to an added R-32 to the edge

ALSO INCLUDED

Fasteners will arrive to the job site with the product.

TESTING

- Tested per ANSI/SPRI/FM 4435/ES-1 Standard to comply with the International Building Code.
- Factory Mutual approved for wind uplift protection.
- Miami-Dade Approved to comply with the High Velocity Hurricane Zone of the Florida Building Code.

ADDITIONAL INFORMATION

On projects where a MuleHide Standard or Premium Warranty is requested, an authorized MuleHide representative shall inspect all completed work.

The information given on this PDS is subject to change without notice. Always check the MuleHide website at www.mulehide.com for the latest information, changes and updates or contact MuleHide at 800-786-1492.

Nailer-T Benefits	Wood Nailer Comparison
Performance protection for wind speeds up to a Category 5 hurricane	No performance guarantee
FM Approved to 1-990, withstanding 1200 psf	Not as structurally strong as heavy gauge aluminum
Heavy gauge extruded aluminum will not warp, crack, split, rot, or deform	Wood deteriorates from moisture, mold, insects, and more
Continuous insulation to the roof edge (up to 47% increase in R-value at the edge)	Prevents insulation from reaching the roof edge, allowing energy to escape and moisture to get in
Easy and precise installation with pre-punched holes, installing up to 60% faster than wood nailers	Wood can be uneven, requiring additional prep time before and during installation
Non-combustible and can be reused when removed	Combustible and serves as a food source for insects and mold

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. ("MuleHide"). Since the manner of use is beyond our control, MuleHide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a MuleHide warranty, please check the MuleHide website at www.mulehide.com or contact MuleHide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury to person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. MuleHide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.