




One Extended Fascia

Fully Adhered or Mechanically Attached Single-Ply Version



PRODUCT DATA SHEET

DESCRIPTION

One Extended Fascia offers quick-to-ship convenience and economical pricing to simplify projects and maximize profits. Our One Extended Fascia for single-ply membrane roofs extends your coverage on the roof edge while protecting against high wind events, saving the building from costly damage. The design eliminates the stripping in typical of other products, making it fast and easy to install and offers larger face heights to accommodate multiple nailers and coverage requirements.

STANDARD MATERIALS

- 22 ga. Steel
- .050" Aluminum
- .063" Aluminum

STANDARD SIZES

- 9.5"
- 11"
- 12.5"

COLORS

Choose from over 30 colors and finishes that meet your job requirements. Finish Warranty is available depending on color selection. See color chart for color and warranty availability.

EFFICIENT DESIGN

- Provided in 12'-0" lengths with pre-punched holes for quicker installation and lower labor costs.
- Slotted fastening holes allow for thermal movement of the materials and ensure correct fastener placement and spacing.
- Snap-on cover with no exposed fasteners, eliminates any strip-in or heat welding.
- Extended sizes to cover up to 7 nailers.

INCLUDED COMPONENTS

- Fascia Cover
- 20 ga. Steel Cleat
- Stainless Steel Springs
- Concealed Splice Plates
- All fasteners included will arrive to the job site with the product

ACCESSORIES

Factory fabricated miters and accessories provide a cleaner, more aesthetically pleasing appearance. This eliminates the need for field fabrication, providing time and labor savings.

CUSTOM CAPABILITIES

Radius is available to meet the unique needs of each project.

TESTING

- Tested per ANSI/SPRI/FM 4435/ES-1 Standard to comply with the International Building Code.
- Factory Mutual approved for wind uplift protection.
- Miami-Dade Approved to comply with the High Velocity Hurricane Zone of the Florida Building Code.

ADDITIONAL INFORMATION

On projects where a MuleHide Standard or Premium Warranty is requested, an authorized MuleHide representative shall inspect all completed work.

The information given on this PDS is subject to change without notice. Always check the MuleHide website at www.mulehide.com for the latest information, changes and updates or contact MuleHide at 800-786-1492.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. ("MuleHide"). Since the manner of use is beyond our control, MuleHide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a MuleHide warranty, please check the MuleHide website at www.mulehide.com or contact MuleHide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury to person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. MuleHide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.