



Si TPO Primer

Primer for New and Aged TPO



PRODUCT DATA SHEET



DESCRIPTION

Si TPO Primer is a primer used to promote adhesion with 100% Silicone Roof Coating to new and aged TPO roofing membranes. Si TPO Primer is manufactured from fast-evaporating solvents and adhesive resins. Primer has a blue color to allow applicator to better gauge application rates.

BASIC USES

MuleHide Si TPO Primer is recommended for priming new and aged TPO roofing membranes to improve adhesion of the finish coat.

PACKAGING

- 4.75-gallon pail (17.9 liters)
- 1-gallon can
- 1-pint can with brush (clear) for use with Shape Shift

TYPICAL PROPERTIES AND CHARACTERISTICS*

Physical Property	Test Method	Value
Solids Volume (%)	ASTM D1683	6.5 ± 1.5
Flash Point (°F)	PMCC	116.6
Maximum VOC (gm/L)	Calculated	42
Weight/gal (lb)	ASTM D1475	10.5 ± 1

*Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification or specification range for any particular property of this product.

INSTALLATION INSTRUCTIONS

PREPARATION

1. Surface must be clean, completely dry and free from any foreign matter such as dirt, oils, grease or other debris that could adversely affect the primer to surface adhesion.
2. Recommended application temperature is 40°F and rising.
3. Do not apply to wet or visibly damp surfaces.

APPLICATION

1. Mix well prior to application.
2. Apply with a short nap roller or brush at the rate of 1-gallon per 300-400 sq. ft.
3. Application should be as thin as possible. Heavier application of the primer will reduce the effectiveness of the primer.
4. Allow Si TPO Primer to dry for one to two hours before top coating.
5. Si TPO Primer must be coated within 48 to 72 hours to prevent surface contamination prior to application of Silicone Roof Coating.
6. Entire surface must be blue in color. Reapply to any areas that are not blue in color.
7. Product dries by solvent evaporation eliminating concern for pot life limitations. Do not allow the primer to set with the lid off for long periods of time as the solvents will dissipate causing the primer to thicken and in turn be discarded.

Application instructions are basic guidelines only. Please read and understand the complete MuleHide specifications for our Silicone Roof Coatings prior to use.

PRECAUTIONS

- WARNING! COMBUSTIBLE LIQUID AND VAPOR.
- Contains petroleum distillates. Keep away from heat and open flames.
- Do not thin.
- Protect from freezing.
- Avoid prolonged contact with skin or inhalation of solvent fumes. A NIOSH approved respirator with organic vapor cartridges is recommended. Do not take internally. If swallowed, do not induce vomiting. Contact medical personnel immediately. For professional use only. Read SDS prior to use.
- **California Proposition 65 Warning:** This product may contain chemicals known to the State of California to cause cancer, birth defects and/or reproductive harm.

For Professional Use Only - Keep out of the reach of children.



Si TPO Primer

Primer for new and aged TPO



PRODUCT DATA SHEET

STORAGE AND CLEANING

- Shelf life is 24 months if stored in original unopened containers.
- All containers should be sealed when not in use.
- Store between 40°F and 100°F.
- If temperatures are cold, store product in a heated area overnight.
- DO NOT HEAT WITH AN OPEN FLAME.
- Observe normal safeguards for storing and handling of this product prior to and during application.
- Clean equipment and overspray with water.
- Clean hands with waterless hand cleaner.
- Application tools and equipment can be cleaned with odorless mineral spirits solvent. Recirculate through lines and spray equipment.
- DO NOT USE WATER OR RECLAIMED SOLVENTS.

MANUFACTURING FACILITIES

- Fernley, NV
- Hazleton, PA
- Phoenix, AZ
- Waco, TX
- Winter Haven, FL

PROTECTION & SAFETY

MuleHide maintains safety data sheets on all of its non-exempt products. Safety data sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. MuleHide's safety data sheets should be read and understood by all of your supervisory personnel and employees before using MuleHide products in your facilities.

ADDITIONAL INFORMATION

On projects where a MuleHide standard or premium warranty is requested, an authorized MuleHide representative shall inspect all completed work.

The information given on this PDS is subject to change without notice. Always check the MuleHide website at www.mulehide.com for the latest information, changes and updates or contact MuleHide at 800-786-1492.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. ("MuleHide"). Since the manner of use is beyond our control, MuleHide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a MuleHide warranty, please check the MuleHide website at www.mulehide.com or contact MuleHide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury to person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. MuleHide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.