




Snap Gold Coping

Tapered, Flat and Existing Slope



PRODUCT DATA SHEET

DESCRIPTION

Snap Gold Coping has a full snap-on design with 16-gauge, galvanized steel anchor clips and factory-applied stainless steel springs that ensure long-term positive attachment, bringing extra stability to the roof edge system. In addition, the snap-on design facilitates fast and easy installation. Snap Gold Coping is custom fabricated in sizes to meet specific job requirements.

VERSIONS

- Tapered
- Flat
- Existing Slope

STANDARD MATERIALS

- 24 ga. Steel
- 22 ga. Steel
- .040" Aluminum
- .050" Aluminum
- .063" Aluminum

SIZES

- Face Size/Outside Face: 3" to 12"
- Back Size/Inside Face: 2.75" to 4" (No testing or approval Max 12")
- Wall Size: 3.5" to 24" (24 ga., .040") 32" (22 ga., .050", .063") (No testing or approval Max 39.875")

COLORS

Choose from over 30 colors and finishes that meet your job requirements. Finish Warranty is available depending on color selection. See color chart for color and warranty availability.

EFFICIENT DESIGN

- Full, snap-on design in 12'-0" lengths with no crimping make for quick installation and lower labor costs.
- 12" wide, steel anchor clips that provide more positive attachment ensuring extra stability for the system. (Anchor clip spacing determined by manufacturer)
- Corrosion resistant, stainless-steel springs are factory attached to the anchor clips and provide long-term, positive spring loading.
- Pre-punched fastening holes ensure proper attachment to the building substrate.
- Concealed splice plates with dual non-curling isocryl butyl sealant strips allow for thermal movement of materials and seals all joints.

INCLUDED COMPONENTS

- Coping Cover
- 16 ga. Steel Anchor Clips
- Concealed Splice Plates
- All fasteners are included and will arrive to the job site with the product.

ACCESSORIES

Factory fabricated miters and accessories provide a cleaner, more aesthetically pleasing appearance. This eliminates the need for field fabrication, providing time and labor savings.

CUSTOM CAPABILITIES

Radius and arched specially fabricated products are available to meet the unique needs of each project.

TESTING

- Tested per ANSI/SPRI/FM 4435/ES-1 Standard to comply with the International Building Code.
- Factory Mutual approved for wind uplift protection.
- Miami-Dade Approved to comply with the High Velocity Hurricane Zone of the Florida Building Code.

ADDITIONAL INFORMATION

On projects where a MuleHide Standard or Premium Warranty is requested, an authorized MuleHide representative shall inspect all completed work.

The information given on this PDS is subject to change without notice. Always check the MuleHide website at www.mulehide.com for the latest information, changes and updates or contact MuleHide at 800-786-1492.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. ("MuleHide"). Since the manner of use is beyond our control, MuleHide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a MuleHide warranty, please check the MuleHide website at www.mulehide.com or contact MuleHide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury to person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. MuleHide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.