



Product Data Sheet

TB-75 & TB-125 STAINLESS STEEL

Revision Date: October 2019

DESCRIPTION

Mule-Hide Termination Bars Stainless Steel (TB) are for use in membrane roofing systems to provide a compression seal for flashing terminations in accordance with various Mule-Hide termination details. The Stainless Steel bars are typically selected when exceptional corrosion resistance is needed.

TYPICAL PHYSICAL PROPERTIES

Physical Properties and Characteristics		
	TB-75 Stainless Steel	TB-125 Stainless Steel
Material	304 Stainless Steel	304 Stainless Steel
Dimensions	.075 x 1" x 10'-0"	.125 x 1" x 10'-0"
Holes	1/4" x 3/8" at 6" OC	1/4" x 3/8" at 6" OC

COLORS

304 Stainless Steel Bar

PACKAGING

TB-75 Stainless Steel 20 pieces per bundle, shipping weight: approx. 51 pounds per tube
TB-125 Stainless Steel 20 pieces per bundle, shipping weight: approx. 98 pounds per tube

STORAGE & HANDLING

Store tubes in a dry location to prevent damage to tube, take care when storing or handling to avoid bending or bowing the bars.

APPLICATION TEMPERATURES

When installing bars in cold weather, care should be taken to provide slightly larger gaps between bar sections to reduce the potential for bowing and buckling when warming occurs.

APPLICATION

- Standard personal protective equipment (PPE) should be used when installing fasteners through the bar into various substrates or when cutting the bar becomes necessary.
- Install bar on approved vertical surfaces at the top of the membrane to be terminated. Follow Mule-Hide's specific termination detail for the membrane type being terminated. Regardless of hole spacing, fasteners must be installed in all pre-punched holes.

PROTECTION & SAFETY

Mule-Hide maintains Safety Data Sheets on all of its non-exempt products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

ADDITIONAL INFORMATION

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at www.mulehide.com for the latest information, changes and updates or contact Mule-Hide Products Company, Inc. at 800-786-1492.

PRODUCT NAME

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a Mule-Hide warranty, please check the Mule-Hide website at www.mulehide.com or contact Mule-Hide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.