



Torch Base SA

Revision Date: Jul 2020

PRODUCT DESCRIPTION

Torch Base SA is a self-adhered, fiberglass reinforced, modified bitumen membrane manufactured to meet the toughest industry and code requirements. Torch Base SA is manufactured using **Adeso**[®] dual-compound technology, where the membrane consists of Styrene Butadiene Styrene (SBS) modified asphalt compound on top and a pressure sensitive adhesive compound on the bottom. The adhesive is covered with a split release liner. Torch Base SA is finished with a polyolefin film with printed lay lines on the top surface. Meets ASTM D4601 Type II / ASTM D1970.



BASIC USES

Torch Base SA membrane is specially designed for applications where the use of hot asphalt, cold process adhesive, or a propane torch is undesirable. Applications include new roofing, recover (retrofit) and BUR repairs. Torch Base SA can be used as a waterproofing base sheet applied to approved roof decks or substrates. Do not apply to shingles, shakes or other residential roofing material. See the Mule-Hide Self-Adhered Modified Bitumen Application Guidelines for complete specifications and details.

SPECIFICATIONS AND PACKAGING

Thickness	Approx. Weight	Roll Size	Rolls/Pallet	Coverage
1.65 mm (65)mils	86 lb./roll	65'8"x39 3/8" (20mx1m)	20	200 ft ²

Physical Property	Test Method	ASTM Values
Elongation at Peak Load at 0°F (-18°C)	ASTM D5147	1%
Peak load at 73°F (23°C)	ASTM D5147	30 lbf/in. (5.3) kN/m
Elongation at Peak Load at 73°F (23°C)	ASTM D5147	2%
Tear strength at 73°F (23°C)	ASTM D5147	35 lbf (156) N
Low temperature flexibility, max, F° (C°)	ASTM D5147	0°F (-18°C)
Adhesion to Plywood @ 40°F (4.4°C)	ASTM D1970	2.0 lbf/ft
Adhesion to Plywood @ 75°F (24°C)	ASTM D1970	12.0 lbf/ft
Sealability around nail	ASTM D1970	Pass
Waterproof integrity after low temp flexibility	ASTM D1970	Pass
Waterproof integrity of lap seam	ASTM D1970	Pass

Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification or specification range for any particular property of this product.

PRODUCT BENEFITS

1. Pre-applied adhesive on the back of the sheet.
2. Durable - high performance reinforcement mat.
3. No hot asphalt, fumes or flames required for installation.
4. Excellent long term adhesion to multiple substrates and to base plies.
5. Offers low-temp flexibility, puncture and tear resistance.

CODE APPROVALS

Product Data Sheet

Torch Base SA

Various code approvals are available including: Underwriters Laboratories, Florida Product Approval, and ICC-ESR. Contact Mule-Hide Technical Department for specific ratings.

INSTALLATION INSTRUCTIONS

Torch Base SA is intended to be used as a base sheet or interplay in new or re-roofing applications, and requires the installation of a granulated cap sheet to complete the roofing system.

1. Nail Base or an approved insulation shall be mechanically attached to a suitable substrate.
 - A. Torch Base SA may be adhered directly to a suitable substrate.
2. Starting at the low point of the roof, install Torch Base SA as follows: Unroll the Torch Base SA and allow it to relax.
3. After positioning the sheet, fold the top half of the sheet back lengthwise, remove the release liner and roll the material back into place, taking care to avoid wrinkles and trapped air, and maintaining proper sheet alignment.
4. Firmly hand press sheet from the center out avoiding wrinkles and trapped air as the Torch Base SA adheres to the Nail Base Sheet, or approved substrate.
5. When completing end laps stagger end laps approximately three feet apart. Cut the top corner of the top sheet on a 45-degree angle (start the cut 3" in from the top edge and finish down 3" from the top edge) and the bottom corner of the bottom sheet on a 45-degree angle (start the cut 3" in from the bottom edge and finish 3" up from the bottom edge). Apply a solid bead of Mod Bit Sealant along both cut edges. Remember to remove the release film from the FASTLap® and SEALLap® edges prior to adhering the lower half of the SA Base Sheet.
6. Repeat procedure to adhere remaining half of the sheet.
7. After the sheet is adhered, it is required to be rolled with a 75 lb. roller, roll in the 3' width first, then the length of the roll can be rolled.
8. Position subsequent sheets to overlap the previous courses by the width of the selvage edge (overlap in a shingle fashion ensuring that laps are water shedding).

This is only a brief summary and NOT the complete specification. The Mule-Hide APP Modified Bitumen Application Guidelines, Specifications, Details, Technical Bulletins, and associated documents should be thoroughly reviewed prior to starting any project.

PROTECTION & SAFETY

Mule-Hide maintains Safety Data Sheets on all of its nonexempt products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

ADDITIONAL INFORMATION

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at www.mulehide.com for the latest information, changes and updates or contact Mule-Hide Products Company at 800-786-1492.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a Mule-Hide warranty, please check the Mule-Hide website at www.mulehide.com or contact Mule-Hide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.

Adeso® Is a registered trademark of Polyglass USA