



## Product Data Sheet

# #102 FIBRATED ROOF COATING

### PRODUCT DESCRIPTION

#102 Fibrated Roof Coating is a fiber reinforced, non-polymer modified asphalt roof coating that forms a flexible, weather resistant film that has excellent adhesion to most surfaces.

### BASIC USES

- Designed to be used on smooth surfaced built-up roofs, polymer-modified (APP, SBS) bituminous membranes, and roll-roofing membranes as a protective coating.
- Performs well as an adhesive for mineral granules.
- Suitable for use as an adhesive for organic roll roofing membranes.
- DO NOT USE with PVC, TPO, EPDM or other single-ply membranes.



### PHYSICAL PROPERTY INFORMATION\*

Property	Method	Value
Weight/gal (lb)	ASTM D2939	7.8 -8.5 lbs. per gallon
Viscosity (Seconds)	550 gm load/100 rev 77°F	30-100
Solids Weight (%)	ASTM D1644	>65
Flash Point (°F)	PMCC	>105°F
VOC (gm/L)	Std method	<300
Sag @140°F	ASTM D6511	Pass
Pliability @ 32°F	ASTM D6511	Pass
Drying Time		Ave. 2-5 hours to touch

\* Data reported is based on available independent and in-house resources. Mule-Hide reserves the right to change or modify, at its discretion, and without prior written notice, any of the information, requirements, specifications or policies contained in this document.

### PACKAGING

4.75 Gallon Pail (18 Liters)

### BENEFITS & SUPPLEMENTAL STATEMENTS

- Safer, more efficient alternative to hot asphalt
- Easy to use

### CODE APPROVALS/COMPLIANCE

- Miami Dade County Approval
- Meets ASTM D3019 Type I
- Meets ASTM D4479 Type I

### COVERAGE RATES

- Approximately 2 to 3 gallons per 100 sq. ft. depending upon job specifications
- Approximately 4 gallons per 100 sq. ft. when used to adhere granules.
- Stir coating to uniform consistency before using.
- Avoid heavy mounds of mass accumulation.  
(All values are approximate and may vary with ambient temperature and job conditions)

# Product Data Sheet

#102 FIBRATED ROOF COATING

---

## INSTALLATION TEMPERATURE

- Apply only when ambient temperatures are 45°F and rising. Cold weather could result in uneven application and improper curing of product. Cold weather will cause product to stiffen making application more difficult.
- Store product at room temperature for minimum 24 hours prior to application.
- Do not heat container or attempt to thin this product.
- Not recommended for application on substrates that exceed 140°F.

## INSTALLATION INSTRUCTIONS

### Surface Preparation:

- All surfaces to be adhered must be clean, dry and free from any foreign matter such as oil, grease, dirt or any debris that could inhibit the bonding capabilities of the newly installed product.
- On existing roofs, inspect roof deck. Blisters, buckles and raised edges should be cut out and repaired for a smooth surface.
- Check all flashing, edges, drains, valleys and vents and repair as needed. On gravel roofs, remove gravel before making repair.
- Do not use on wet or damp surfaces, directly over wood or on surfaces previously covered with coal tar based products.

### Installation Method:

- Stir well prior to application.
- Product may be applied by roller, squeegee, or stiff bristle brush. Apply product in a uniform, continuous film and brush well in both directions to ensure complete, even coverage. Avoid heavy mounds of mass accumulation.
- Drying time is approximately 48 hours in warm, dry weather.

## PRECAUTIONS

### COMBUSTIBLE LIQUID AND VAPOR

- Contains petroleum distillate. Harmful or fatal if swallowed. Close container after each use. **DO NOT TAKE INTERNALLY!** Vapor harmful. May affect the brain or central nervous system causing dizziness, headache, or nausea. Causes nose and throat irritation. Causes eye irritation. Causes skin irritation. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Keep away from heat and open flame.
- Use only with adequate ventilation. **CLOSE AIR INTAKES** on roof until solvents dissipate. Do not breathe vapors. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.
- **California Proposition 65 Warning:** This product may contain chemicals know to the State of California to cause cancer, birth defects and/or reproductive harm.

**Personal Protection** – Irritation may result from prolonged or repeated contact with skin. Wear chemical resistant gloves, protective goggles and protective clothing, if needed.

**Eye Contact** – Rinse immediately with clean water for 15 minutes and see medical advice.

**Waste Disposal** – Empty containers must be disposed of in accordance with local, state, and federal regulations.

**For Professional Use Only** – Keep out of the reach of children.

**For Exterior Use Only** - Refer to material safety data sheet (MSDS) for specific data and handling.

## CLEAN UP

- Clean tools with mineral spirits or paint thinner.

# Product Data Sheet

#102 FIBRATED ROOF COATING

---

## **STORAGE & HANDLING**

- Product shelf life is 24 months from date of manufacture when properly stored.
- Store container at room temperature for minimum 24 hours prior to use.
- Do not store at temperatures greater than 120°F.
- Observe normal safeguards for storing and handling of product prior to and during use.
- Keep containers tightly covered when not in use.

## **MANUFACTURING FACILITIES**

- Fernley, NV
- Hazleton, PA
- Winter Haven, FL

## **PROTECTION & SAFETY**

Mule-Hide maintains Safety Data Sheets on all of its non-exempt products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

## **ADDITIONAL INFORMATION**

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at [www.mulehide.com](http://www.mulehide.com) for the latest information, changes and updates or contact Mule-Hide Products Company, Inc. at 800-786-1492.

## **DISCLAIMER**

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.