




DensDeck® StormX™ Prime Roof Board



PRODUCT DATA SHEET



DESCRIPTION

DensDeck StormX Prime Roof Board is a reinforced gypsum cover board with an enhanced, moisture-resistant core and coated glass mat facers. DensDeck StormX is extremely durable and is approved for use in assemblies meeting FM's Very Severe Hail (VSH) Classification.

BENEFITS AND SUPPLEMENTAL STATEMENTS

- Provides added protection from excessive foot traffic, wind, and hail
- First gypsum cover board to meet FM VSH classification under single-ply membranes
- Approved as a thermal barrier over combustible and non-combustible roof decks
- Achieves UL 790 Class A and FM Class 1 approvals
- Manufactured to meet the "Type X" requirements of ASTM C1177

PACKAGING

- 5/8" - 4'x4' Panels - 34 pieces - 1632 lbs.
- 5/8" - 4'x8' Panels - 26 pieces - 2496 lbs.

STORAGE

When stored outside or at the job site, the roof board must be stored at least 4" above ground level and completely covered with a weatherproof covering such as a tarpaulin. **Warning - Do Not Leave Exposed:** Product must be kept dry at all times. Install only as much roof board as can be covered the same day by the roofing system.

TYPICAL PHYSICAL PROPERTIES

Property	5/8" (15.9 mm)
Thickness, nominal	5/8" (15.9 mm) ±1/32" (1.6 mm)
Width, Standard	4' (1219 mm) ±1/8" (3 mm)
Length, Standard	4' (1219 mm) 8' (2438 mm) ±1/4" (6.4 mm)
Weight, lbs/sq ft (kg/m ²) ⁷	3.0 (14.6)
Surfacing	Fiberglass Mat with non-asphaltic coating
Flexural Strength ¹ , parallel, lbf. Min. (N)	100 (444)
Flute Spanability ²	8" (203 mm)
Permeance ³ , perms (ng/Pa•S•m ²)	>17 (>970)
R Value ⁴ , ft ² •°F•hr/BTU (m ² K/W)	0.67
Linear Variation with Change in Temp., in/in °F (mm/mm/°C)	8.5 x 10 ⁻⁶ (15.3 x 10 ⁻⁶)
Linear Variation with Change in Moisture	6.25 x 10 ⁻⁶
Water Absorption ⁵ , %	5
Compressive Strength ⁶ , psi nominal	900
Surface Water Absorption, rams, nominal ¹	1.0
Flame Spread, Smoke Developed (ASTM E84)	10 (highest possible)
Bending Radius	ASTM C1177

1 Tested in accordance with ASTM C473 method B.

2 Tested in accordance with ASTM E661.

3 Tested in accordance with ASTM E96 (dry cup method)

4 Tested in accordance with ASTM C518 (heat flow meter).

5 Tested in accordance with ASTM C1177.

6 Tested in accordance with ASTM C473.

7 When tested, as manufactured, in accordance with ASTM D3273, DensDeck Roof Boards have scored a 10, the highest level of performance for mold resistance under the ASTM D3273 test method. The score of 10, in the ASTM D3273 test, indicates no mold growth in a 4-week controlled laboratory test. The mold resistance of any building product when used in actual jobsite conditions may not produce the same results as were achieved in the controlled, laboratory settings.


CODE APPROVALS/COMPLIANCE

DensDeck StormXTM Roof Boards are manufactured to meet ASTM C1177 and meet the following standards and classifications:

- Type X
- ANSI/UL 790 and ULC-CAN S114 Classification – Class A (unlimited slope)
- UL 1256 Classification
- FM Class 1
- When used as part of a UL 1256 or FM 4450 classified system, no additional thermal barrier is required per IBC



DensDeck® StormX™ Prime Roof Board



PRODUCT DATA SHEET

INSTALLATION INSTRUCTIONS

DensDeck StormX may be secured with Helix Max Adhesive, fastened in accordance with an approved fastening pattern, or mopped with hot asphalt.

Maximum asphalt application temperatures of 425°F (218°C) to 450°F (232°C) are recommended. Application temperatures above these recommended temperatures may adversely affect roof system performance.

Edge joints should be located on and parallel to deck ribs. End joints of adjacent lengths should be staggered.

1. This material shall be installed with ends and edges butted tightly.
2. When installed over combustible wood decks or insulations, all joints should be staggered.
3. In accordance with approved shop drawings, FM-approved fasteners shall be installed with plates through the roof board, flush with the surface.
4. When attaching F5 Air and Vapor Barrier, use DensDeck StormX in conjunction with CCW-702, 702LV, or AeroWeb Adhesive.

Review MuleHide specifications and details for complete installation information.

PRECAUTIONS

- When applying solvent-based adhesives or primers, allow sufficient time for the solvents to flash off.
- ¼" DensDeck is not recommended for vertical parapet applications or for asphalt attachment.
- In ballasted roofing systems, DensDeck is not an acceptable membrane underlayment.

PROTECTION & SAFETY

MuleHide maintains safety data sheets on all of its non-exempt products. Safety data sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. MuleHide's safety data sheets should be read and understood by all of your supervisory personnel and employees before using MuleHide products in your facilities.

ADDITIONAL INFORMATION

The information given on this PDS is subject to change without notice. Always check the MuleHide website at www.mulehide.com for the latest information, changes and updates or contact MuleHide at 800-786-1492.

DensDeck is a registered trademark of Georgia-Pacific Gypsum LLC.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. ("MuleHide"). Since the manner of use is beyond our control, MuleHide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a MuleHide warranty, please check the MuleHide website at www.mulehide.com or contact MuleHide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury to person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. MuleHide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.