



Gravel Stop

PVC or TPO Coated Version



PRODUCT DATA SHEET

DESCRIPTION

Gravel Stop offers quick-to-ship convenience and economical pricing to simplify projects and maximize profits. Gravel Stop is made with PVC or TPO coated metal and specifically designed to simplify the installation process and further save costs. It is available in convenient 10' (PVC) or 12' (TPO) lengths with pre-slotted fastening holes.

STANDARD COVER MATERIALS

- 24 ga. Steel with PVC or TPO coated metal

SIZES

- Min: 2.5"
- Max: 10"

STANDARD COLOR

- White

EFFICIENT DESIGN

- Provided in 10'-0" (PVC) or 12'-0" (TPO) lengths with pre-punched holes for quicker installation and lower labor cost.
- Slotted fastening holes to allow for proper thermal movement of the materials and ensure correct fastener placement and spacing.

ACCESSORIES

Factory fabricated miters and accessories provide a cleaner, more aesthetically pleasing appearance. This eliminates the need for field fabrication, providing time and labor savings.

INCLUDED COMPONENTS

- Gravel Stop Cover
- 22 ga. Steel Continuous Cleat
- All fasteners will arrive to the job site with the product

CUSTOM CAPABILITIES

Radius is available to meet the unique needs of each project.

TESTING

- Tested per ANSI/SPRI/FM 4435/ES-1 Standard to comply with the International Building Code.
- Factory Mutual approved for wind uplift protection.
- Miami-Dade approved to comply with the High Velocity Hurricane Zone of the Florida Building Code.

ADDITIONAL INFORMATION

The information given on this PDS is subject to change without notice. Always check the MuleHide website at www.mulehide.com for the latest information, changes and updates or contact MuleHide at 800-786-1492.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. ("MuleHide"). Since the manner of use is beyond our control, MuleHide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a MuleHide warranty, please check the MuleHide website at www.mulehide.com or contact MuleHide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury to person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. MuleHide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.