



LWG 3-Inch Metal Plate

Superior Wind Uplift Resistance



PRODUCT DATA SHEET

DESCRIPTION

MuleHide's LWG 3" metal plates are used to mechanically attach insulation, cover boards and base sheets to lightweight insulating concrete (LWIC) and gypsum decks. The LWG 3" metal plate is a circular design with one center fastener placement hole and eight equally spaced fastener placement holes around the perimeter of the plate allowing for maximum versatility. Required pull out values can be achieved by installing multiple LWG fasteners in one LWG 3" metal plate.

ACCESSORIES

LWG 3" metal plates are designed to be used with LWG fasteners.

SPECIFICATIONS	
Material	20 ga. Galvalume coated metal
Coating	Galvalume AZ-50
Thickness	0.017"
Hold Diameter	0.260"
Packaging	1,000/Bucket
Weight	34 lb.

INSTALLATION INSTRUCTIONS

LWG 3" metal plates are designed for use with LWG fasteners. Project specific pull tests are required. Depending on pull out values, more than one LWG fastener may be required to achieve the desired minimum pullout resistance. Multiple fasteners may be installed in the LWG 3" metal plate increasing the amount of force required to pull the plate/fastener assembly out of the approved deck. Approved fastener patterns are available in detail MHU-LWG-1. Contact MuleHide Technical Department for additional assistance.

LEED® INFORMATION	
Eligible Recycled Content	20%
Manufacturing Location	Cleveland, OH


PROTECTION & SAFETY

MuleHide maintains safety data sheets on all of its non-exempt products. Safety data sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. MuleHide's safety data sheets should be read and understood by all of your supervisory personnel and employees before using MuleHide products in your facilities.

ADDITIONAL INFORMATION

On projects where a MuleHide standard or premium warranty is requested, an authorized MuleHide representative shall inspect all completed work.

The information given on this PDS is subject to change without notice. Always check the MuleHide website at www.mulehide.com for the latest information, changes and updates or contact MuleHide at 800-786-1492.



DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. ("MuleHide"). Since the manner of use is beyond our control, MuleHide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a MuleHide warranty. Please check the MuleHide website at www.mulehide.com or contact MuleHide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury to person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. MuleHide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.