



MP Liquid Sealant

Roofing Sealant



PRODUCT DATA SHEET



DESCRIPTION

MP Liquid Sealant is a single-component, non-shrink, advanced technology polyurethane sealant designed for filling pitch pans and sealing seams, endlaps, fasteners and flashings on metal roof systems prior to applying acrylic coatings.

It may be used in conjunction with ShapeShift™ straight and corner sections which can be combined to produce pitch pans of various sizes and shapes. It has adequate viscosity to avoid running on steep-slope application and drain-out issues that are encountered with less viscous sealers. MP Liquid Sealant is 100% solids which results in zero shrinkage. Temperature performance range is -40°F to +200°F.

PACKAGING

2-liter pouches packaged 4 to a bucket

COVERAGE

As a penetration pocket filler:

- One, 2-liter pouch will fill approximately two, 6-inch sealant pockets. Specific coverage rates are based on sealant pocket size (Shape Shift, TPO molded) and will vary due to the number of penetrations within the pocket.

On Metal Panel roofs in conjunction with Acrylic coating:

- 1-gal/150 linear feet of seam and applied @ 1-gallon/ 350-450 fasteners

INSTALLATION INSTRUCTIONS

Preparation

1. All surfaces must be clean and dry prior to application.

TYPICAL PHYSICAL PROPERTIES

Property	Value*
Chemistry	Polyether
Viscosity (cps @ 10 rpm)	87,500
Density (lbs/gal)	13.6
Hardness (Shore A)	54
Skinover time @ 50% RH/70°F	20 min
VOC's (g/L)	18
Elongation at Break (%)	105
Tensile Strength (psi)	179
Shrinkage (%)	0
Peel Strength (lbf/in)	ABC Plastic - 11 Acrylic - 8 Aluminum - 10 Glass - 8 Mortar - 6 Pine - 5 PVC - 10

*Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification or specification range for any particular property of this product.

Application to fill pitch pans

1. Surfaces must be free of moisture, dirt and any contaminants. Any previously applied asphalt, caulking or sealants must be removed from the penetration.
2. Fill any voids in the roof deck around the penetration(s) to prevent sealant from seeping through the roof. Pourable sealer must be a minimum of 2" (50mm) deep. All penetrations must be a minimum of 1" (25mm) from sides of the pitch pan or sealer pocket.
3. Unscrew the pouch and pour MP Liquid Sealant directly into pocket. Fill pocket completely until rim is covered with MP Liquid Sealant making sure all voids are filled.
4. Primer may be required to ensure a long lasting bond and weatherproof seal.

PRECAUTIONS

- CAUTION: Do not take internally. If swallowed, do not induce vomiting. Keep out of reach of children. Read SDS prior to use.
- California Proposition 65 Warning: This product may contain chemicals known to the State of California to cause birth defects and/or reproductive harm.

CLEAN UP

Clean up with Naptha



MP Liquid Sealant

Roofing Sealant



PRODUCT DATA SHEET

STORAGE & HANDLING

- One year shelf life with proper storage.
- Store in a cool, dry place.
- High temperatures and high humidity during storage will shorten the products shelf life.

PROTECTION & SAFETY

MuleHide maintains safety data sheets on all of its non-exempt products. Safety data sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. MuleHide's safety data sheets should be read and understood by all of your supervisory personnel and employees before using MuleHide products in your facilities.

ADDITIONAL INFORMATION

On projects where a MuleHide standard or premium warranty is requested, an authorized MuleHide representative shall inspect all completed work.

The information given on this PDS is subject to change without notice. Always check the MuleHide website at www.mulehide.com for the latest information, changes and updates or contact MuleHide at 800-786-1492.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. ("MuleHide"). Since the manner of use is beyond our control, MuleHide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a MuleHide warranty, please check the MuleHide website at www.mulehide.com or contact MuleHide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury to person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. MuleHide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.