



Product Data Sheet

MULTIBASE SB

PRODUCT DESCRIPTION

Rev. April 2023

Multibase SB is a primer and stain blocker for use on approved substrates/surfaces prior to the application of the 100% Silicone Roof Coating. This allows for improved adhesion. It is formulated to a relatively thin viscosity which allows for excellent penetration on most roof surfaces. This is a water-based material and must be kept from freezing.

BASIC USES

Multibase SB is intended for application as a primer to concrete, modified bitumen, asphalt BUR, PVC, EPDM and Hypalon roof surfaces prior to applying the 100% Silicone Roof Coatings. Do not use on coal-tar-pitch roofs, TPO membranes or any areas of ponding water. Contact Mule-Hide's Technical Services Department for additional information.

TYPICAL PHYSICAL PROPERTIES

Property*	Method	Value
Viscosity (cP)	Brookfield@ 4d/5 RPM/77°F	11,000
Weight / gal (lb)	ASTM D2939	9.3
Solids Weight (%)	ASTM D1644	48
Solids Volume (%)	ASTM D2697	44
VOC (gm/L)	Calculated	< 10

*Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.

COLORS

The standard color is Mint Green.

PACKAGING

Packaging is standard in 5-gallon pail (18.9 Liter), 55-gallon drum (208.1 Liter).

ALL ACRYLIC COATINGS MUST BE PROTECTED FROM FREEZING AT ALL TIMES.

APPLICATION EQUIPMENT

Application may be by brush, roller, or airless spray.

1. Brush: Suitable for small areas and flashings. Use a soft bristle paint brush.
2. Roller: Recommended when coating small areas. Use a medium (1/2") or a long (1.0") napped roller.
3. Airless Spray Equipment: Multibase SB can be applied by conventional airless spray equipment designed for the purpose of field application of fluids, paints and coatings. The following minimums are recommended:
 - Pump: 1.6 gal/min output; 2,500 psi
 - Gun/Tip: Airless handgun. Reversible tip with orifice sizes ranging from 0.19—0.25 and a fan angle of 40° or 50°.
 - Hose: Minimum inside diameter of high-pressure nylon hose of 3/8" to 100'; for any hose over 200' the inside diameter should be 1/2".
 - Refer to equipment manufacturer product guidelines.

Product Data Sheet

MULTIBASE SB

APPLICATION

Application Temperatures

- Temperature of surfaces to be coated should be above 40°F and rising and below 110°F. Do not apply material if the humidity is greater than 90% or there is a threat of rain within 48 hours. Do not apply if there is a chance that ambient temperatures may drop below 45°F within 48 hours after application.
- Check weather conditions prior to start of work. Mule-Hide Acrylic Coatings require complete evaporation of water to cure. Cool temperatures and high humidity retard cure. Do not apply if weather conditions will not permit complete cure before rain, dew or freezing temperatures.

Surface Preparation

- All surfaces to receive coating must be clean, dry and free from any foreign matter such as dirt, oils, grease or other debris that could inhibit the adhesion capabilities of the newly installed products.
- Metal surfaces that display rusting or other oxidation, to be prepared with a grinder or wire brush as needed to remove surface contaminants.
- Existing roof systems to be visually inspected for conditions that may adversely affect adhesion or performance of newly installed products. Repair any visible deficiencies such as splitting blistering and buckling prior to the installation of the coating system.
- Visually inspect all metal and non-metal flashings, edges, drains, valleys and through-roof penetrations and repair as needed by project conditions.
- **Do not apply** to wet or visibly damp surfaces, surfaces previously covered with coal tar-based products, Kynar® finishes, TPO membranes or any areas of ponding water.
- Concrete surfaces cured with wax/resin-based compounds can inhibit adhesion.

Installation

- Mechanically mix before using.
- All surfaces to be coated with the Multibase SB must be power washed clean with Mule-Hide 115 Cleaner and allowed to dry. The surface may be damp but must be free of all standing water.
- Surface temperatures should be under 100°F to avoid premature curing.
- Apply with a soft bristle brush, roller or suitable spray equipment at the following recommended rates:

Substrate	Coverage Rate*
Galvanized Steel	1/2 gallon per 100 sf
Aluminum	1/2 gallon per 100 sf
Bituminous, granulated membranes	2/3 – 1 gallon per 100 sf
Wood	1/2 – 2/3 gallon per 100 sf
Concrete / Masonry	1/2 – 2/3 gallon per 100 sf
Single-Plies (EPDM, TPO, PVC)	1/2 – 1 gallon per 100 sf

*When applying over asphalt surfaces, more product may be required on alligatored or irregular surfaces. Irregular surfaces may require a prime coat to fill in and level the roof surface.

- Do not apply this product to any surfaces that pond water more than 48 hours. The service life will be severely diminished and adhesion failure can be expected.
- Mule-Hide recommends approximately 12 hours cure time between coats or the product should be sufficiently dry that foot traffic will not damage the coating. Multiple coats should always be applied within 72 hours of each coat to minimize or prevent contamination that would require additional cleaning.
- Protection of areas not intended to be coated, or items such as, skylights, HVAC units, etc., must be protected by masking or covering to prevent over spray or accidental coating. The applicator will be responsible for any material spills, spray drift, or over spray.
- Commencement of work by the contractor confirms his approval of the deck or existing roof surface.

Product Data Sheet

MULTIBASE SB

STORAGE AND CLEANING

- Product Shelf Life: Typically 18 months from date of manufacture when properly stored.
- Do not store at temperatures greater than 120°F.
- Store 24 hours at room temperature prior to application.
- Observe normal safeguards for storing and handling of this product prior to and during application.
- Do not allow product to freeze. Discard if any degree of freezing would occur.
- Keep containers covered when not in use.
- Clean equipment and over spray with water.
- Clean hands with waterless hand cleaner.

For Professional Use Only - Keep out of the reach of children.

MANUFACTURING FACILITIES

- Fernley, NV
- Hazleton, PA
- Phoenix, AZ
- Waco, TX
- Winter Haven, FL

PROTECTION & SAFETY

Mule-Hide maintains Safety Data Sheets on all of its non-exempt products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

ADDITIONAL INFORMATION

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at www.mulehide.com for the latest information, changes and updates or contact Mule-Hide Products Company at 800-786-1492.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a Mule-Hide warranty, please check the Mule-Hide website at www.mulehide.com or contact Mule-Hide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.