



PVC Coated Metal

Fabricate Metal Drip Edges or Other Edging Profiles



PRODUCT DATA SHEET

DESCRIPTION

MuleHide PVC Coated Metal is a 24-gauge, galvanized steel sheet that is coated with a layer of 0.035" non-reinforced PVC flashing.

BASIC USES

PVC Coated Metal is cut into the appropriate width and used to fabricate metal drip edges or other roof perimeter edging profiles. PVC membrane may be welded directly to the coated metal edging, eliminating the need to strip in the metal with a separate piece of membrane.

BENEFITS AND SUPPLEMENTAL STATEMENTS

- Allows direct welding of PVC membrane to metal
- Easy to cut and form for creating a variety of edge sizes and shapes
- Available in White, Gray, Light Gray, Slate Gray and Tan colors
- Matches membrane color to create a uniform appearance

INSTALLATION INSTRUCTIONS

1. Install PVC coated metal with 1/8" to 1/4" (3 to 6 mm) wide joints between adjoining sections.
2. Install 2" wide (5 cm) foil tape over joints in PVC metal (to act as a bond breaker).
3. Heat-weld a minimum 6" wide (15.5 cm) strip of PVC non-reinforced flashing membrane over joint.
4. Position PVC reinforced membrane and heat-weld to PVC clad metal achieving a min 1-1/2" wide weld. Review MuleHide specifications and details for additional installation information.

STORAGE AND HANDLING

Store coated metal in a cool, shaded area and cover with light-colored, breathable, waterproof tarpaulins.

PRECAUTIONS

- PVC Coated Metal that has been exposed to the weather must be prepared with Weathered Membrane Cleaner prior to hot-air welding.
- Do not allow membrane side of PVC Coated Metal to come in contact with asphalt, coal tar pitch, polystyrene, or other petroleum-based products.

PROTECTION & SAFETY

MuleHide maintains safety data sheets on all of its non-exempt products. Safety data sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. MuleHide's safety data sheets should be read and understood by all of your supervisory personnel and employees before using MuleHide products in your facilities.

TYPICAL PROPERTIES AND CHARACTERISTICS

Sheet Size	4' x 10' (1.2 m x 3.0 m)
Weight	1.1 lb/ft ² (5.4 kg/m ²)
Color	White, Tan, Light Gray, Gray, and Slate Gray
Flashing Thickness	0.035" (0.9 mm) nominal
Steel Thickness	0.024" (0.6 mm) nominal
Steel Type	Hot Dipped Galvanized Steel-G90
Packaging	10 Sheets per pallet

*Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification or specification range for any particular property of this product.

LEED INFORMATION

Pre-consumer Recycled Content	0%
Post-consumer Recycled Content	0%
Manufacturing Location	Scranton, PA
Solar Reflectance Index (SRI)	White: 111 Tan: 50 Light Gray: 90 Gray: 43 Slate Gray: Pending

ADDITIONAL INFORMATION

On projects where a MuleHide standard or premium warranty is requested, an authorized MuleHide representative shall inspect all completed work.

The information given on this PDS is subject to change without notice. Always check the MuleHide website at www.mulehide.com for the latest information, changes and updates or contact MuleHide at 800-786-1492.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. ("MuleHide"). Since the manner of use is beyond our control, MuleHide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a MuleHide warranty, please check the MuleHide website at www.mulehide.com or contact MuleHide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury to person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. MuleHide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.