




# Snap Coping

Tapered, Flat and Existing Slope



## PRODUCT DATA SHEET

**NOTE: FM APPROVAL AND MIAMI-DADE APPROVAL WILL NOT BE AVAILABLE AT INITIAL LAUNCH. APPLICATIONS PENDING.**



### DESCRIPTION

Continuing a tradition of innovative, tested roof edge systems, Snap Coping is a fine complement to your building's natural aesthetics for parapet conditions. It features steel anchor clips, a snap-on cover, and is available in variety of options for different wall conditions. Snap Coping is exactly what you need for your building: the right design, the right quality, the right price—and easy to install.

### PRODUCT HIGHLIGHTS

- ANSI/SPRI/FM 4435/ES-1 Tested
- Factory Mutual Approved
- Miami-Dade Approved
- Available in a variety of colors, sizes, and materials
- No exposed fasteners
- Easy installation resulting in decreased labor costs
- Prefabricated miters and accessories to prevent need for field fabrication

### VERSIONS

- Tapered, Flat and Existing Slope

### STANDARD COVER MATERIALS

- 24 ga. Steel
- 22 ga. Steel
- .040" Aluminum
- .050" Aluminum
- .063" Aluminum

### SIZES

#### Face Size / Outside Face

- 3" to 6" (Tested/Approved)
- No Testing or Approvals: Max 12"

#### Back Size / Inside Face

- 2.25" to 4" (Tested/Approved)
- No Testing or Approvals: Max 12"

#### Wall Size

- 3.5" to 16" (Tested/Approved)
- No Testing or Approvals: Max 39.875"

### COLORS

Choose from over 30 colors and finishes that meet your job requirements. Finish Warranty is available depending on color selection. See color chart for color and warranty availability.

### EFFICIENT DESIGN

- Full, snap-on design in 12'-0" lengths with no crimping make for quick installation and lower labor costs.
- 12" wide, steel anchor clips that provide more positive attachment ensuring extra stability for the system. (Anchor clip spacing determined by manufacturer)
- Corrosion resistant, stainless-steel springs are factory attached to the anchor clips and provide long-term, positive spring loading.
- Pre-punched fastening holes ensure proper attachment to the building substrate.
- 8" wide concealed splice plates with dual non-curling isocryl butyl sealant strips allow for thermal movement of materials and seals all joints.


### ACCESSORIES

Factory fabricated miters and accessories provide a cleaner, more aesthetically pleasing appearance. This eliminates the need for field fabrication, providing time and labor savings.



# Snap Coping

Tapered, Flat and Existing Slope



## PRODUCT DATA SHEET

### INCLUDED COMPONENTS

- Coping Cover
- 20 ga. Steel Anchor Clips
- Concealed Splice Plates
- All fasteners are included and will arrive to the job site with the product

### CUSTOM CAPABILITIES

Radius and arched specially fabricated products are available to meet the unique needs of each project.

### TESTING

- Tested per ANSI/SPRI/FM 4435/ES-1 Standard to comply with the International Building Code.
- Factory Mutual approved for wind uplift protection.
- Miami-Dade Approved to comply with the High Velocity Hurricane Zone of the Florida Building Code.

### ADDITIONAL INFORMATION

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at [www.mulehide.com](http://www.mulehide.com) for the latest information, changes and updates or contact Mule-Hide Products Company at 800-786-1492.

### DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a Mule-Hide warranty, please check the Mule-Hide website at [www.mulehide.com](http://www.mulehide.com) or contact Mule-Hide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made