



Product Data Sheet

Shur-Gard #40 Base Sheet

Rev. Mar 2021

DESCRIPTION

Shur-Gard #40 Base Sheet is manufactured from superior quality felt that is saturated with asphalt and then coated on both sides with weathering grade coating asphalt and then covered on top with mineral surface fines to prevent sticking in the roll. Meets ASTM 2626-04



BASIC USES

- Applied over the flat roofing deck or insulation before the application of Built-Up Roofing systems.

TYPICAL PHYSICAL PROPERTIES

Physical Properties and Typical Performance	
Physical Property	Typical Results
Roll Width	39.375"
Roll Length	65'
Coverage per roll	214 sqft
Roll Weight	80 lbs.
Mass of Base Sheet	37.0 lbs/100 sqft
Mass of Asphalt Saturant	7.2 lbs/ 100 sqft
Mass of Desaturated Felt	5.2 lbs/ 100 sqft
Mass of Coating and Surfacing (min)	18.0 lbs/ sqft
Mass per Side of Asphalt Coating (Back Coating)	3.5 lbs/ sqft
Saturation Efficiency (min) by Weight Breaking Strength at 77° (min)	100%
Machine Direction	35 lbf/in
Cross Direction	20 lbf/in
Water Vapor Permeance	0.3 grains/hr. ftsq (in Hg) 1/2" radius

PACKAGING

25 rolls per pallet

PROTECTION & SAFETY

Mule-Hide maintains Safety Data Sheets on all of its non-exempt products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

Shur-Gard #40 Base Sheet

ADDITIONAL INFORMATION

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at www.mulehide.com for the latest information, changes and updates or contact Mule-Hide Products Co., Inc. at 800-786-1492.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a Mule-Hide warranty, please check the Mule-Hide website at www.mulehide.com or contact Mule-Hide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.