



# Walkway Granules

Provides a Non-Slip Surface

## PRODUCT DATA SHEET

### DESCRIPTION

Walkway Granules are colored EPDM granules specially formulated to provide a non-slip surface over a MuleHide Silicone Roof Coating.

### BASIC USES

Used to provide a non-slip surface for walkways and traffic areas where foot traffic is expected on a MuleHide Silicone Roof Coating. Walkway Granules may be embedded in the surface of the silicone roof coating to provide a more durable, damage and slip resistant surface.

### COLOR

Yellow.

### PACKAGING

Container size: 5-Gallon (30 lbs.)

### APPLICATION INSTRUCTIONS

1. Walkway Granules are to be broadcast into surface of freshly applied MuleHide 100% Silicone Roof Coating at the rate of 15 lbs per 100 square feet. Apply enough granules to completely cover the wet silicone coating.
2. Do not allow Silicone Roof Coating to skim over or granules will not adhere.
3. Loose granules may be vacuumed off after Silicone Roof Coating has cured. Vacuuming of loose granules is recommended to help prevent accumulation of loose granules in gutters or drain.
4. Over time, walkway surface may wear, but it can easily be repaired or resurfaced by applying additional Silicone Roof Coating and new granules.
5. The outline of the intended walkway area can be taped off to provide a straight border to improve the appearance of the walkway. Remove the tape prior to the product drying.

Application instructions are basic guidelines only. Please read and understand the complete MuleHide specification for our Silicone products prior to use.

### PRECAUTIONS

Avoid prolonged contact with skin. If irritation occurs seek medical attention. Keep out of reach of children. For professional use only. Read SDS prior to use.

### CLEAN UP

Loose granules can be vacuumed from the roof surface.

### STORAGE & HANDLING

Five year shelf life with proper storage.

Job site storage in excess of 90°F (32°C) may affect product shelf life. Store product at temperatures between 60°F and 80°F. Materials exposed to lower temperatures affect the workability and performance of the product. Products must be restored to 60°F prior to use.

### PROTECTION & SAFETY

MuleHide maintains Safety Data Sheets on all of its non-exempt products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. MuleHide's Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using MuleHide products in your facilities.

### ADDITIONAL INFORMATION

On projects where a MuleHide Standard or Premium Warranty is requested, an authorized MuleHide representative shall inspect all completed work.

The information given on this PDS is subject to change without notice. Always check the MuleHide website at [www.mulehide.com](http://www.mulehide.com) for the latest information, changes and updates or contact MuleHide at 800-786-1492.

### DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. ("MuleHide"). Since the manner of use is beyond our control, MuleHide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a MuleHide warranty, please check the MuleHide website at [www.mulehide.com](http://www.mulehide.com) or contact MuleHide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. MuleHide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.