



# PVC Overlayment Strip

Revision Date: November 2019

## DESCRIPTION

Mule-Hide's PVC Overlayment Strip is a 60-mil non-reinforced thermoplastic polyvinyl chloride-based membrane enhanced with KEE HP used for stripping in KEE HP Coated Metal roof edging.



## FEATURES AND BENEFITS

- High Flexibility allows for easier installation
- 6"-wide rolls eliminates the need to slit flashing material and saves labor

## TYPICAL PHYSICAL PROPERTIES

Typical Properties and Characteristics		
Properties	ASTM Test Method	Specification
Tolerance on nominal Thickness	ASTM D751	±8
Weight, lb/ft <sup>2</sup> (kg/m <sup>2</sup> ), typical	N/A	0.44 lb/ft <sup>2</sup>
Breaking strength, min, lbf/in. (N)	ASTM D751 Proc. B	167.60 (MD), 142.88 (CD)
Elongation at Break, min., %	ASTM D751 Proc. B	399.60 (MD), 420.27 (CD)
Tear strength, min., lbf/in (kN/m)	ASTM D1004	10
Heat aging: 28 days % Retention	ASTM D4434	90
Resistance to Xenon-Arc weathering Xenon-Arc, 5,040 kJ/m <sup>2</sup> total radiant Exposure, visual condition at 7X	ASTM D4434	"No cracking/ crazing, negligible discoloration"

\*Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.

## COLORS

White/Gray or White/Tan to match white, gray, or tan Mule-Hide PVC or KEE HP reinforced membranes

## PACKAGING

6" x 100' rolls

## STORAGE & HANDLING

Store Mule-Hide PVC Overlayment Strip in a cool, shaded area and cover with light-colored, breathable, waterproof tarpaulins.

## PRECAUTIONS

- Surfaces may be slippery when wet, or due to frost and ice build-up. Exercise caution to prevent falls.
- Mule-Hide PVC membranes are highly reflective to sunlight. Workers should dress appropriately, wear sunscreen, and wear sunglasses that filter out UV light.
- Exercise care when working near roof edge. Roof edges may not be visible when surrounding area is

# PRODUCT NAME

---

- covered with snow.
- Store Mule-Hide membrane in original wrappings in a cool, shaded area. Cover with light-colored, breathable, waterproof tarpaulins. Mule-Hide membrane that has been exposed to the elements for approximately 7 days or longer must be prepared with PVC Membrane Cleaner prior to hot air welding.

## **APPLICATION**

1. Ensure the existing PVC, KEE HP membrane, or Coated Metal surface is clean prior to welding the Overlayment Strip in place. If dirt is present, use Mule-Hide's PVC Membrane Cleaner to properly prepare the surface.
2. Weld Overlayment Strip in place using an automatic welder or hand-welder.
3. Use the edge of a hand-held silicone roller to crease the flashing into any membrane step-off for a proper seal.

## **LEED INFORMATION**

<b>LEED® Information</b>	
<b>Pre-consumer Recycled Content</b>	<b>10%</b>
<b>Post-consumer Recycled Content</b>	<b>0%</b>
<b>Manufacturing Location</b>	<b>Mountain Top, PA</b>
<b>Solar Reflectance Index</b>	<b>111 (white), 69 (gray), 81 (tan)</b>

## **PROTECTION & SAFETY**

Mule-Hide maintains Safety Data Sheets on all of its non-exempt products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

## **ADDITIONAL INFORMATION**

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at [www.mulehide.com](http://www.mulehide.com) for the latest information, changes and updates or contact Mule-Hide Products Company at 800-786-1492.

## **DISCLAIMER**

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a Mule-Hide warranty, please check the Mule-Hide website at [www.mulehide.com](http://www.mulehide.com) or contact Mule-Hide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.