Safety Data Sheet 10-8505 102 FIBRATED ROOF COATING

Safety Data Sheet dated: 01/19/2023 - version 2

Date of first edition: 11/11/2022

MULE-HIDE PRODUCTS

1. IDENTIFICATION

Product identifier

Mixture identification:

Trade name: 102 FIBRATED ROOF COATING

Trade code: PLY0111

Recommended use of the chemical and restrictions on use

Recommended use: Bituminous mastics solvent based

Restrictions on use: Not available

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: MULE HIDE PRODUCTS CO. INC.

1195 PRINCE HALL DRIVE, BELOIT, WI, 53511. USA

Phone: 800-786-1492

Responsable: www.mulehide.com Emergency 24 hour numbers:

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887 Emergency Transport CANUTEC (Canada) 1-613-996-

6666

2. HAZARD(S) IDENTIFICATION







Classification of the chemical

Flammable Liquids — Category 3 Flammable liquid and vapour.

Skin irritation, Category 2

Causes skin irritation.

Eye irritation, Category 2A

Causes serious eye irritation.

Germ cell mutagenicity, Category 1B May cause genetic defects if inhaled, in contact with skin and if

swallowed.

Carcinogenicity, Category 1A May cause cancer if inhaled, in contact with skin and if

swallowed.

Specific target organ toxicity following repeated exposure,

Category 1

Causes damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed.

Acute aquatic hazard, category 3

Chronic (long term) aquatic hazard, category 3

Harmful to aquatic life

Harmful to aquatic life with long lasting effects.

Label elements

Pictograms and Signal Words



Danger

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H340 May cause genetic defects if inhaled, in contact with skin and if swallowed.

H350 May cause cancer if inhaled, in contact with skin and if swallowed.

H372 Causes damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if

swallowed.

H402 Harmful to aquatic life

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

Date 1/19/2023 Production Name 102 FIBRATED ROOF COATING Page n. 1 of 9

P201	Obtain special instructions before use.			
P202	Do not handle until all safety precautions have been read and understood.			
P210	Keep away from heat/sparks/open flames/hot surfaces. — No smoking.			
P233	Keep container tightly closed.			
P240	Ground/bond container and receiving equipment.			
P241	Use explosion-proof electrical/ventilating/lighting equipment.			
P242	Use only non-sparking tools.			
P243	Take precautionary measures against static discharge.			
P260	Do not breathe mist/vapours/spray.			
P264	Wash skin thoroughly after handling.			
P270	Do not eat, drink or smoke when using this product.			
P273	Avoid release to the environment.			
P280	Wear protective gloves/protective clothing/eye protection/face protection.			
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.			
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.			
P308+P313	IF exposed or concerned: Get medical advice/attention.			
P314	Get medical advice/attention if you feel unwell.			
P321	Specific treatment (see supplementary instructions on this label)			
P332+P313	If skin irritation occurs: Get medical advice/attention.			
P337+P313	If eye irritation persists: Get medical advice/attention.			
P362+P364	Take off contaminated clothing and wash it before reuse.			
P370+P378	In case of fire, use a dry powder fire extinguisher to extinguish.			
P403+P235	Store in a well-ventilated place. Keep cool.			
P405	Store locked up.			
P501	Dispose of contents/container in accordance with applicable regulations.			
Ingredient(s) with unknown acute toxicity:				

Ingredient(s) with unknown acute toxicity:

None

D201

Hazards not otherwise classified identified during the classification process:

Obtain enocial instructions before use

None

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substances

Not Relevant

Mixtures

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components

Qty	Name	Ident. Numb.	Classification	Registration Number
1-2.5 %	petroleum hydrocarbons; Stoddard Solvent	EC:232-489-3	Flam. Liq. 3, H226; STOT RE 1, H372; Asp. Tox. 1, H304; Muta. 1B, H340; Carc. 1B, H350	

4. FIRST AID MEASURES

Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an opthalmologist immediately.

Date 1/19/2023 Production Name 102 FIBRATED ROOF COATING Page n. 2 of 9

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

Most important symptoms/effects, acute and delayed

Eye irritation

Eye damages

Skin Irritation

Ervthema

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media:

Unsuitable extinguishing media:

None in particular.

Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not available Oxidizing properties: Not available

Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

7. HANDLING AND STORAGE

Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Conditions for safe storage, including any incompatibilities

Handle in a well ventilated place.

Always keep in a well ventilated place.

Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

Store in a well-ventilated place. Keep cool.

Avoid direct exposure to sunlight.

Date 1/19/2023 Production Name 102 FIBRATED ROOF COATING Page n. 3 of 9

Opened containers must be carefully resealed and kept upright to prevent leakage.

Flammable mixtures may accumulate within the headspace of containers at room temperature.

Storage at higher temperatures requires an appropriate evaluation of preventive and protection measures to be adopted.

Storage temperature must be defined on the basis of a proper risk evaluation. Refer to other sections for additional information.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Electrical installations / working materials must comply with the technological safety standards.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system.

Storage temperature: Not available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Community Occupational Exposure Limits (OEL)

OEL Occupational Exposure Limit

Type

petroleum hydrocarbons;

OSHA Long Term: 2900 mg/m3 - 500 ppm

Stoddard Solvent CAS: 8052-41-3

ACGIH Long Term: 100 ppm

CNS impairment; eye, kidney and skin damage; nausea;

ACGIH Long Term: 100 ppm

CNS impairment; eye, kidney and skin damage; nausea

Appropriate engineering controls: Not available

Individual protection measures

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105:

Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min.

Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min.

Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min.

Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: liquid Black

Odour: hydrocarbons like

Odour threshold: No data available

pH: No data available

Melting point / freezing point: No data available Initial boiling point and boiling range: 179 °C (354 °F)

Flash point: 40.5 °C (104.9 °F) Evaporation rate: No data available

Upper/lower flammability or explosive limits: 3.55 % w/w

Date 1/19/2023 Production Name 102 FIBRATED ROOF COATING Page n. 4 of 9

Vapour density: >1

Vapour pressure: No data available Relative density: 0.95 g/cm3 Solubility in water: Insoluble Solubility in oil: no data available

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available Decomposition temperature: No data available

Viscosity: No data available

Explosive properties: No data available Oxidizing properties: No data available Solid/gas flammability: data not applicable

Other information

Substance Groups relevant properties Not normally reactive

Miscibility: No data available Fat Solubility: No data available Conductivity: No data available

10. STABILITY AND REACTIVITY

Reactivity

Stable

It may generate dangerous reactions (See subsections below)

Chemical stability

It may generate dangerous reactions (See subsections below)

Possibility of hazardous reactions

It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.

Conditions to avoid

Heat and open flames.

Avoid accumulating electrostatic charge.

Incompatible materials

Water

Avoid contact with combustible materials. The product could catch fire.

Hazardous decomposition products

Develop toxic gases when heated to decomposition.

11. TOXICOLOGICAL INFORMATION

Information on toxicological effects

Toxicological Information of the Preparation

a) acute toxicity Not classified

b) skin corrosion/irritation

The product is classified: Skin irritation, Category 2(H315)

c) serious eye damage/irritation

The product is classified: Eye irritation, Category 2A(H319)

d) respiratory or skin sensitisation Not classified

Based on available data, the classification criteria are not met

e) germ cell mutagenicity The product is classified: Germ cell mutagenicity, Category 1B(H340)

f) carcinogenicity The product is classified: Carcinogenicity, Category 1A(H350)

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure The product is classified: Specific target organ toxicity following repeated exposure,

Category 1(H372)

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

Toxicological information on main components of the mixture:

petroleum hydrocarbons; a) acute toxicity

Stoddard Solvent

LD50 Skin Rabbit > 3000 mg/kg

Date 1/19/2023 Production Name 102 FIBRATED ROOF COATING Page n. 5 of 9

Substance(s) listed on the IARC Monographs:

None

Substance(s) listed as OSHA Carcinogen(s):

None

Substance(s) listed as NIOSH Carcinogen(s):

None

Substance(s) listed on the NTP report on Carcinogens:

None

12. ECOLOGICAL INFORMATION

Toxicity

Adopt good working practices, so that the product is not released into the environment.

Eco-Toxicological Information:

List of Eco-Toxicological properties of the product

The product is classified: Acute aquatic hazard, category 3(H402), Chronic (long term) aquatic hazard, category 3(H412)

Persistence and degradability

NΑ

Bioaccumulative potential

N.A.

Mobility in soil

N.A.

Other adverse effects

N.A.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

14. TRANSPORT INFORMATION

UN number

DOT-UN Number: NA1993 ADR-UN number: 1993 IATA-Un number: 1993 IMDG-Un number: 1993

UN proper shipping name

DOT-Proper Shipping Name: COMBUSTIBLE LIQUID, N.O.S. (solvent naphtha - 1,2,4-trimethyl-benzene; pseudocumene) (Not regulated for US DOT if shipped by road in non-bulk containers of 119 gallons or less)

Date 1/19/2023 Production Name 102 FIBRATED ROOF COATING Page n. 6 of 9

ADR-Shipping Name: FLAMMABLE LIQUID, N.O.S. (having a flash-point below 23 °C and viscous according to 2.2.3.1.4) (vapour

pressure at 50 °C more than 110 kPa, boiling point of more than 35 °C) (solvent naphtha - 1,2,4-trimethyl-

benzene; pseudocumene)

IATA-Technical name: FLAMMABLE LIQUID, N.O.S. (solvent naphtha - 1,2,4-trimethyl-benzene; pseudocumene) IMDG-Technical name: FLAMMABLE LIQUID, N.O.S. (solvent naphtha - 1,2,4-trimethyl-benzene; pseudocumene)

Transport hazard class(es)

DOT-Hazard Class: COMBUSTIBLE

ADR-Class: 3
IATA-Class: 3
IMDG-Class: 3

Packing group

DOT-Packing group: III ADR-Packing Group: III IATA-Packing group: III IMDG-Packing group: III

Environmental hazards

Marine pollutant: No

Environmental Pollutant: Not Applicable

DOT-RQ: No

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

Special precautions

Department of Transportation (DOT):

DOT-Special Provision(s): 148, IB3, T1, TP1

DOT-Label(s): NONE
DOT-Symbol: D G
DOT-Cargo Aircraft:

DOT-Cargo Aircraft: 220 L DOT-Passenger Aircraft: 60 L DOT-Bulk: 241

DOT-Non-Bulk: 203
Road and Rail (ADR-RID):
ADR-Label: 3

ADR-Hazard identification number: 30

ADR-Transport category (Tunnel restriction code): 3 (D/E)

Air (IATA):

IATA-Passenger Aircraft: 355 IATA-Cargo Aircraft: 366

IATA-Label: 3

IATA-Subsidiary hazards: -

IATA-Erg: 3L

IATA-Special Provisions: A3

Sea (IMDG):

IMDG-Stowage Code: Category A

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisions: 223 274 955

IMDG-Page: N/A IMDG-Label: N/A IMDG-EMS: F-E, S-E IMDG-MFAG: N/A

Pursuant to 49 CFR 173.120(b)(2) and 49 CFR 173.150(f) a flammable liquid with a flash point at or above 100 degrees Fahrenheit may be reclassed as a combustible liquid for transportation within the U.S. by motor vehicle or rail only.

15. REGULATORY INFORMATION

USA - Federal regulations

TSCA - Toxic Substances Control Act

TSCA inventory:

All the components are listed on the TSCA inventory

TSCA listed substances:

Date 1/19/2023 Production Name 102 FIBRATED ROOF COATING Page n. 7 of 9

petroleum hydrocarbons; Stoddard is listed in TSCA Section 8b Solvent

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

No substances listed

Section 313 - Toxic chemical list:

No substances listed

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act Substance(s) listed under CERCLA:

No substances listed

CAA - Clean Air Act

CAA listed substances:

No substances listed

CWA - Clean Water Act

CWA listed substances:

No substances listed

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

No substances listed

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

petroleum hydrocarbons; Stoddard Solvent

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

petroleum hydrocarbons; Stoddard Solvent

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

petroleum hydrocarbons; Stoddard Solvent

Canada - Federal regulations

DSL - Domestic Substances List

DSL (Domestic Substances List)

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

NDSL (Non Domestic Substances List)

No substances listed

NPRI - National Pollutant Release Inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

16. OTHER INFORMATION

Safety Data Sheet dated: 1/19/2023 - version 2

Additional classification information

NFPA Health: 1 = Slight

NFPA Flammability: 2 = Combustible liquid

NFPA Reactivity: 0 = Minimal NFPA Special Risk: NONE



NFPA

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Date 1/19/2023 Production Name 102 FIBRATED ROOF COATING Page n. 8 of 9

H350	May cause cancer.				
H372	Causes damage to organs through prolonged or repeated exposure.				
Code	Hazard class and hazard category	Description			
A.10/1	Asp. Tox. 1	Aspiration hazard, Category 1			
A.5/1B	Muta. 1B	Germ cell mutagenicity, Category 1B			
A.6/1B	Carc. 1B	Carcinogenicity, Category 1B			
A.9/1	STOT RE 1	Specific target organ toxicity following repeated exposure, Category 1			
B.6/3	Flam. Liq. 3	Flammable Liquids — Category 3			

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

Description

Flammable liquid and vapour.

May cause genetic defects.

May be fatal if swallowed and enters airways.

Code

H226

H304 H340

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. WGK: German Water Hazard Class.

KSt: Explosion coefficient.

Paragraphs modified from the previous revision:

- 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING
- 3. COMPOSITION/INFORMATION ON INGREDIENTS
- 8. EXPOSURE CONTROLS/PERSONAL PROTECTION
- 11. TOXICOLOGICAL INFORMATION
- 12. ECOLOGICAL INFORMATION
- 14. TRANSPORT INFORMATION
- 15. REGULATORY INFORMATION
- 16. OTHER INFORMATION

Date 1/19/2023 Production Name 102 FIBRATED ROOF COATING Page n. 9 of 9