## Safety Data Sheet 10-8580

#### 410 PREMIUM NON-FIBRATED ALUMINUM ROOF COATING

Safety Data Sheet dated: 02/21/2023 - version 4

Date of first edition: 10/21/2021



## 1. IDENTIFICATION

#### **Product identifier**

Mixture identification:

Trade name: 410 PREMIUM NON-FIBRATED ALUMINUM ROOF COATING

Trade code: PLY0086

Recommended use of the chemical and restrictions on use

Recommended use: Coating Restrictions on use: Not available

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Company: MULE HIDE PRODUCTS CO. INC.

1195 PRINCE HALL DRIVE, BELOIT, WI, 53511. USA

Phone: 800-786-1492

Responsable: www.mulehide.com **Emergency 24 hour numbers:** 

Emergency Number (USA/Canada) CHEMTREC 1(800) 424-9300 / 1(703) 527-3887 Emergency Transport CANUTEC (Canada) 1-613-996-

6666

## 2. HAZARD(S) IDENTIFICATION





#### Classification of the chemical

Flammable Liquids — Category 3 Flammable liquid and vapour.

Germ cell mutagenicity, Category 1B May cause genetic defects if inhaled, in contact with skin and if

swallowed.

Carcinogenicity, Category 1B May cause cancer if inhaled, in contact with skin and if

swallowed.

Specific target organ toxicity following repeated exposure,

Category 1

Causes damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if swallowed.

Chronic (long term) aquatic hazard, category 3

Harmful to aquatic life with long lasting effects.

## Label elements

## **Pictograms and Signal Words**



Danger

# **Hazard statements**

H226 Flammable liquid and vapour.

H340 May cause genetic defects if inhaled, in contact with skin and if swallowed.

H350 May cause cancer if inhaled, in contact with skin and if swallowed.

H372 Causes damage to organs through prolonged or repeated exposure if inhaled, in contact with skin and if

swallowed.

H412 Harmful to aquatic life with long lasting effects.

# **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

Date 2/21/2023 Production Name MH 410 PREMIUM NON-FIBRATED ALUMINUM ROOF COATING Page n. 1 of 10

P242	Use only non-sparking tools.	
P243	Take precautionary measures against static discharge.	
P260	Do not breathe mist/vapours/spray.	
P264	Wash skin thoroughly after handling.	
P270	Do not eat, drink or smoke when using this product.	
P273	Avoid release to the environment.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
P308+P313	IF exposed or concerned: Get medical advice/attention.	
P314	Get medical advice/attention if you feel unwell.	
P370+P378	In case of fire, use a dry powder fire extinguisher to extinguish.	
P403+P235	Store in a well-ventilated place. Keep cool.	
P405	Store locked up.	
P501	Dispose of contents/container in accordance with applicable regulations.	

# Ingredient(s) with unknown acute toxicity:

## Hazards not otherwise classified identified during the classification process:

None

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### **Substances**

Not Relevant

# **Mixtures**

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

## List of components

Qty	Name	Ident. Numb.	Classification	Registration Number
25-50 %	petroleum hydrocarbons; Stoddard Solvent	d CAS:8052-41-3 EC:232-489-3 Index:649-345- 00-4	Flam. Liq. 3, H226; STOT RE 1, H372; Asp. Tox. 1, H304; Muta. 1B, H340; Carc. 1B, H350	
5-10 %	naphtha (petroleum), hydrodesulfurized heavy	EC:265-185-4	Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336; Aquatic Chronic 2, H411	
2.5-5 %	naphthenic oil; Low boiling point naphtha - unspecified	CAS:64742-95-6 EC:265-199-0 Index:649-356- 00-4	Asp. Tox. 1, H304; Flam. Liq. 3, H226; Carc. 1B, H350	
1-2.5 %	1,2,4-trimethyl-benzene; pseudocumene	CAS:95-63-6 EC:202-436-9 Index:601-043- 00-3	Flam. Liq. 3, H226; Eye Irrit. 2A, H319; STOT SE 3, H335; Skin Irrit. 2, H315; Aquatic Chronic 2, H411; Acute Tox. 4, H332	

# **4. FIRST AID MEASURES**

## **Description of first aid measures**

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose of safely.

In case of eyes contact:

Wash immediately with water.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

If breathing is irregular or stopped, administer artificial respiration.

In case of inhalation, consult a doctor immediately and show him packing or label.

# Most important symptoms/effects, acute and delayed

Not available

## Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

## 5. FIRE-FIGHTING MEASURES

## **Extinguishing media**

Suitable extinguishing media:

#### Unsuitable extinguishing media:

None in particular.

## Specific hazards arising from the chemical

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not available Oxidizing properties: Not available

#### Special protective equipment and precautions for fire-fighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

#### **6. ACCIDENTAL RELEASE MEASURES**

#### Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

## Methods and material for containment and cleaning up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

## 7. HANDLING AND STORAGE

#### Precautions for safe handling

Avoid contact with skin and eyes, inhalation of vapours and mists.

Exercise the greatest care when handling or opening the container.

Use localized ventilation system.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

## Conditions for safe storage, including any incompatibilities

Store cool and dry.

Always keep in a well ventilated place.

Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

Store in a well-ventilated place. Keep cool.

Avoid direct exposure to sunlight.

Opened containers must be carefully resealed and kept upright to prevent leakage.

Flammable mixtures may accumulate within the headspace of containers at room temperature.

Storage at higher temperatures requires an appropriate evaluation of preventive and protection measures to be adopted.

Storage temperature must be defined on the basis of a proper risk evaluation. Refer to other sections for additional information.

Avoid accumulating electrostatic charge.

Keep away from food, drink and feed.

Electrical installations / working materials must comply with the technological safety standards.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

2/21/2023

Date

Take precautionary measures against static discharge.

Production Name MH 410 PREMIUM NON-FIBRATED ALUMINUM ROOF COATING

Page n. 3 of 10

Incompatible materials:

None in particular.

Instructions as regards storage premises:

Cool and adequately ventilated.

Safety electric system. Storage temperature: Not available

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Control parameters**

## **Community Occupational Exposure Limits (OEL)**

DEL Type

Petroleum hydrocarbons; OSHA

CAS: 8052-41-3

Occupational Exposure Limit

Country Decupational Exposure Limit

Long Term: 2900 mg/m3 - 500 ppm

ACGIH Long Term: 100 ppm

CNS impairment; eye, kidney and skin damage; nausea;

ACGIH Long Term: 100 ppm

CNS impairment; eye, kidney and skin damage; nausea

1,2,4-trimethyl-benzene; EU Long Term: 100 mg/m3 - 20 ppm

pseudocumene CAS: 95-63-6 Behaviour Indicative

MAK GERMANY Long Term: 100 mg/m3 - 20 ppm

MAK AUSTRIA Long Term: 100 mg/m3 - 20 ppm; Short Term: 150 mg/m3 - 30 ppm

Appropriate engineering controls: Not available

#### **Individual protection measures**

Eye protection:

Use close fitting safety goggles, don't use eye lens.

Protection for skin:

Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.

Protection for hands:

Suitable materials for safety gloves; 29 CFR 1910.138 - ANSI/ISEA 105: Polychloroprene - CR: thickness >=0,5mm; breakthrough time >=480min. Nitrile rubber - NBR: thickness >=0,35mm; breakthrough time >=480min. Butyl rubber - IIR: thickness >=0,5mm; breakthrough time >=480min. Fluorinated rubber - FKM: thickness >=0,4mm; breakthrough time >=480min.

Use impervious gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.

Respiratory protection:

Respiratory protection must be used where exposure levels exceed workplace exposure limits. Refer to 29 CFR 1910.134 - CSA Z94.4 for information on selection and use of appropriate respiratory protection equipment.

Use adequate protective respiratory equipment.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

#### Information on basic physical and chemical properties

Physical state: Liquid

Appearance and colour: liquid alluminium Odour: Like: Hydrocarbons, aliphatic Odour threshold: No data available

pH: No data available

Melting point / freezing point: No data available Initial boiling point and boiling range: 179 °C (354 °F)

Flash point: 40.5 °C (104.9 °F) Evaporation rate: No data available

Upper/lower flammability or explosive limits: No data available

Vapour density: No data available

Vapour pressure: 2.00 (kPa 50>C) mmHg @ 68F

Relative density: No data available Solubility in water: Insoluble Solubility in oil: no data available

Partition coefficient (n-octanol/water): No data available

Auto-ignition temperature: No data available Decomposition temperature: No data available

Viscosity: No data available

Explosive properties: No data available Oxidizing properties: No data available Solid/gas flammability: No data available

#### Other information

Substance Groups relevant properties No data available

Miscibility: No data available Fat Solubility: No data available Conductivity: No data available

#### 10. STABILITY AND REACTIVITY

#### Reactivity

Stable

It may generate dangerous reactions (See subsections below)

#### Chemical stability

It may generate dangerous reactions (See subsections below)

#### Possibility of hazardous reactions

It may catch fire on contact with oxidising mineral acids, and powerful oxidising agents.

#### **Conditions to avoid**

Heat and open flames.

Avoid accumulating electrostatic charge.

#### **Incompatible materials**

Avoid contact with combustible materials. The product could catch fire.

## **Hazardous decomposition products**

Data not available.

#### 11. TOXICOLOGICAL INFORMATION

#### Information on toxicological effects

## **Toxicological Information of the Preparation**

a) acute toxicity Not classified

Based on available data, the classification criteria are not met

Based on available data, the classification criteria are not met

c) serious eye damage/irritation Not classified

Based on available data, the classification criteria are not met

d) respiratory or skin sensitisation Not classified

Based on available data, the classification criteria are not met

e) germ cell mutagenicity The product is classified: Germ cell mutagenicity, Category 1B(H340)

f) carcinogenicity The product is classified: Carcinogenicity, Category 1B(H350)

g) reproductive toxicity Not classified

Based on available data, the classification criteria are not met

h) STOT-single exposure Not classified

Based on available data, the classification criteria are not met

i) STOT-repeated exposure The product is classified: Specific target organ toxicity following repeated exposure,

Category 1(H372)

j) aspiration hazard Not classified

Based on available data, the classification criteria are not met

## Toxicological information on main components of the mixture:

a) acute toxicity

petroleum hydrocarbons; a) acute toxicity

Stoddard Solvent

LD50 Skin Rabbit > 3000 mg/kg

LC50 Inhalation Rat > 5.5 mg/l 4h

naphtha (petroleum),

hydrodesulfurized heavy

LD50 Skin Rabbit > 3160 mg/kg

LD50 Oral Rat > 5000 mg/kg

Date 2/21/2023 Production Name MH 410 PREMIUM NON-FIBRATED ALUMINUM ROOF COATING Page n. 5 of 10

naphthenic oil; Low boiling point naphtha - a) acute toxicity

LD50 Skin Rabbit > 2000 mg/kg

unspecified

LC50 Inhalation Rat = 3400 ppm 4h

LD50 Oral Rat = 8400 mg/kg

1,2,4-trimethyl-benzene; a) acute toxicity

pseudocumene

LD50 Skin Rabbit > 3160 mg/kg

LC50 Inhalation Rat = 18 g/m3 4h LD50 Oral Rat = 3280 mg/kg LC50 Inhalation Rat = 18 g/m3 4h

## Substance(s) listed on the IARC Monographs:

None

Substance(s) listed as OSHA Carcinogen(s):

None

Substance(s) listed as NIOSH Carcinogen(s):

None

Substance(s) listed on the NTP report on Carcinogens:

None

## 12. ECOLOGICAL INFORMATION

#### **Toxicity**

Component

Adopt good working practices, so that the product is not released into the environment. Eco-Toxicological Information:

#### List of Eco-Toxicological properties of the product

The product is classified: Chronic (long term) aquatic hazard, category 3(H412)

## List of Eco-Toxicological properties of the components

naphthenic oil; Low boiling point					
naphtha - unspecified					

Ident. Numb.

CAS: 64742-95-6 - EINECS:

CAS: 64742-95- G: LC50 Avian Colinus virginianus > 6500 ppm 5d IUCLID

265-199-0 -INDEX: 649-356-00-4

G: LD50 Avian Colinus virginianus > 2250 mg/kg IUCLID

a) Aquatic acute toxicity : LC50 Fish Oncorhynchus mykiss = 9.22 mg/L 96h

IUCLID

Ecotox Data

a) Aquatic acute toxicity: EC50 Daphnia Daphnia magna = 6.14 mg/L 48h

IÚCLÍD

1,2,4-trimethyl-benzene; pseudocumene

CAS: 95-63-6 -EINECS: 202-436-9 - INDEX: 601-043-00-3 G: LC50 Avian Colinus virginianus > 6500 ppm 5d IUCLID

G: LD50 Avian Colinus virginianus > 2250 mg/kg IUCLID

a) Aquatic acute toxicity: LC50 Fish Pimephales promelas 7.19 mg/L 96h EPA a) Aquatic acute toxicity: EC50 Daphnia Daphnia magna = 6.14 mg/L 48h

IÚCLÍD

# Persistence and degradability

N.A.

## **Bioaccumulative potential**

N.A.

# Mobility in soil

#### Other adverse effects

N.A.

#### 13. DISPOSAL CONSIDERATIONS

#### **Waste treatment methods**

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

#### Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

#### Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

#### Special precautions

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

#### 14. TRANSPORT INFORMATION

#### **UN** number

DOT-UN Number: NA1993 ADR-UN number: 1993 IATA-Un number: 1993 IMDG-Un number: 1993

#### **UN proper shipping name**

DOT-Proper Shipping Name: COMBUSTIBLE LIQUID, N.O.S. (solvent naphtha - mineral spirit) (Not regulated for US DOT if shipped by road in non-bulk containers of 119 gallons or less)

ADR-Shipping Name: FLAMMABLE LIQUID, N.O.S. (having a flash-point below 23 °C and viscous according to 2.2.3.1.4) (vapour

pressure at 50 °C more than 110 kPa, boiling point of more than 35 °C) (solvent naphtha - mineral spirit)

IATA-Technical name: FLAMMABLE LIQUID, N.O.S. (solvent naphtha - mineral spirit) IMDG-Technical name: FLAMMABLE LIQUID, N.O.S. (solvent naphtha - mineral spirit)

## Transport hazard class(es)

DOT-Hazard Class: COMBUSTIBLE

ADR-Class: 3
IATA-Class: 3
IMDG-Class: 3

# **Packing group**

DOT-Packing group: III ADR-Packing Group: III IATA-Packing group: III IMDG-Packing group: III

## **Environmental hazards**

Marine pollutant: No

Environmental Pollutant: Not Applicable

DOT-RO: No

# Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not Applicable

## Special precautions

Department of Transportation (DOT):

DOT-Special Provision(s): 148, IB3, T1, TP1

DOT-Label(s): NONE DOT-Symbol: D G

DOT-Cargo Aircraft: 220 L DOT-Passenger Aircraft: 60 L

DOT-Bulk: 241

DOT-Non-Bulk: 203 Road and Rail (ADR-RID):

ADR-Label: 3

ADR-Hazard identification number: 30

ADR-Transport category (Tunnel restriction code): 3 (D/E)

Air (IATA):

IATA-Passenger Aircraft: 355 IATA-Cargo Aircraft: 366

IATA-Label: 3

IATA-Subsidiary hazards: -

IATA-Erg: 3L

IATA-Special Provisions: A3

Sea (IMDG):

IMDG-Stowage Code: Category A

IMDG-Stowage Note: -

IMDG-Subsidiary hazards: -

IMDG-Special Provisions: 223 274 955

IMDG-Page: N/A IMDG-Label: N/A IMDG-EMS: F-E, S-E IMDG-MFAG: N/A

Pursuant to 49 CFR 173.120(b)(2) and 49 CFR 173.150(f) a flammable liquid with a flash point at or above 100 degrees Fahrenheit may be reclassed as a combustible liquid for transportation within the U.S. by motor vehicle or rail only.

## 15. REGULATORY INFORMATION

#### **USA - Federal regulations**

#### **TSCA - Toxic Substances Control Act**

## **TSCA** inventory:

All the components are listed on the TSCA inventory

## **TSCA listed substances:**

petroleum hydrocarbons; Stoddard is listed in TSCA Section 8b

Solvent

naphtha (petroleum), is listed in TSCA Section 8b

hydrodesulfurized heavy

naphthenic oil; Low boiling point is listed in TSCA Section 8b

naphtha - unspecified

1,2,4-trimethyl-benzene; is listed in TSCA Section 8b

pseudocumene

## **SARA - Superfund Amendments and Reauthorization Act**

# **Section 302 - Extremely Hazardous Substances:**

No substances listed

# Section 304 - Hazardous substances:

No substances listed

## Section 313 - Toxic chemical list:

1,2,4-trimethyl-benzene; pseudocumene

# CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act Substance(s) listed under CERCLA:

No substances listed

#### CAA - Clean Air Act

## **CAA listed substances:**

No substances listed

## **CWA - Clean Water Act**

# **CWA listed substances:**

No substances listed

# USA - State specific regulations California Proposition 65

Date 2/21/2023

## Substance(s) listed under California Proposition 65:

No substances listed

## Massachusetts Right to know

## Substance(s) listed under Massachusetts Right to know:

petroleum hydrocarbons; Stoddard Solvent 1,2,4-trimethyl-benzene; pseudocumene

## Pennsylvania Right to know

## Substance(s) listed under Pennsylvania Right to know:

petroleum hydrocarbons; Stoddard Solvent 1,2,4-trimethyl-benzene; pseudocumene

#### New Jersey Right to know

#### Substance(s) listed under New Jersey Right to know:

petroleum hydrocarbons; Stoddard Solvent 1,2,4-trimethyl-benzene; pseudocumene

#### Canada - Federal regulations

#### **DSL - Domestic Substances List**

DSL (Domestic Substances List)

All the substances are listed in the DSL.

#### **NDSL - Non Domestic Substances List**

**NDSL (Non Domestic Substances List)** 

No substances listed

## **NPRI - National Pollutant Release Inventory**

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

#### **16. OTHER INFORMATION**

Safety Data Sheet dated: 2/21/2023 - version 4

## **Additional classification information**

NFPA Health: 1 = Slight

NFPA Flammability: 2 = Combustible liquid

NFPA Reactivity: 0 = MinimalNFPA Special Risk: N.A.



Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description		
H226	Flammable liquid and vapour.		
H304	May be fatal if swallowed and enters airways.		
H315	Causes skin irritation.		
H319	Causes serious eye irritation.		
H332	Harmful if inhaled.		
H335	May cause respiratory irritation.		
H336	May cause drowsiness or dizziness.		
H340	May cause genetic defects.		
H350	May cause cancer.		
H372	Causes damage to organs through prolonged or repeated exposure.		
H411	Toxic to aquatic life with long lasting effects.		
Code	Hazard class and hazard category	Description	
A.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4	
A.10/1	Asp. Tox. 1	Aspiration hazard, Category 1	
A.2/2	Skin Irrit. 2	Skin irritation, Category 2	

Eye Irrit. 2A Eye irritation, Category 2A A.3/2A Muta. 1B A.5/1B

Germ cell mutagenicity, Category 1B A.6/1B Carc. 1B Carcinogenicity, Category 1B

A.8/3STOT SE 3 Specific target organ toxicity following single exposure, Category 3 STOT RE 1 A.9/1Specific target organ toxicity following repeated exposure, Category 1

Flammable Liquids — Category 3 B.6/3Flam. Liq. 3

Aquatic Chronic 2 US-HAE/C2 Chronic (long term) aquatic hazard, category 2

# Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany. LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit. STOT: Specific Target Organ Toxicity. WGK: German Water Hazard Class.

KSt: Explosion coefficient.

## Paragraphs modified from the previous revision:

- 14. TRANSPORT INFORMATION