

Material Name: Low-VOC PVC Step 2 Primer SDS 10-3227

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name

Low-VOC PVC Step 2 Primer

Synonyms

Primer

Chemical Family

Primer, mixture

Product Use

Solvent primer

Restrictions on Use

For industrial use only.

Manufacturer Information

Carlisle SynTec 1285 Ritner Highway Carlisle, PA 17013 USA Phone: +1-800-479-6832

Emergency Phone #: +1-800-424-9300 (Chemtrec)

Supplier Information:

Mule-Hide Products Co., Inc. 1195 Prince Hall Drive Beloit, WI 53512

USA

Phone: 800-786-1492

Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.

Flammable Liquids - Category 3
Skin Corrosion/Irritation - Category 2
Serious Eye Damage/Eye Irritation - Category 2A
Skin Sensitization - Category 1A
Carcinogenicity - Category 2
Specific Target Organ Toxicity - Single Exposure - Category 3
Specific Target Organ Toxicity - Repeated Exposure - Category 2 (liver,kidneys)

GHS Label Elements

Symbol(s)







Signal Word Warning

Page 1 of 13 Issue date: 2018-10-09 Revision 1.0



Material Name: Low-VOC PVC Step 2 Primer SDS 10-3227

Hazard Statement(s)

Flammable liquid and vapor

Causes skin irritation

Causes serious eye irritation

May cause allergic skin reaction

Suspected of causing cancer

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure

Precautionary Statement(s)

Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Keep container tightly closed

Keep away from heat/sparks/open flame/hot surfaces - No smoking

Ground/Bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting equipment

Take precautionary measures against static discharge

Use only non-sparking tools

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

Do not breathe dust/fume/gas/mist/vapours/spray

Wash thoroughly after handling

Contaminated work clothing must not be allowed out of the workplace

Response

In case of fire: Use appropriate media to extinguish IF exposed or concerned: Get medical advice/attention

IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing

Call a POISON CENTER or doctor if you feel unwell

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with

water/shower

If skin irritation or rash occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

Specific treatment (see label)

Storage

Keep container tightly closed

Store in a well-ventilated place. Keep cool

Store locked up

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

Page 2 of 13 Issue date: 2018-10-09 Revision 1.0



Material Name: Low-VOC PVC Step 2 Primer SDS 10-3227

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

CAS	Component Name	Percent		
64742-89-8	Solvent naphtha, petroleum, light aliphatic	10-30		
Trade Secret	Isophorone Diisocyanate	0.5-1.5		
108-88-3	Toluene	3-7		
Trade Secret	Chlorinated polypropylene	0.1-1		
98-56-6	PCBTF	60-100		
Trade Secret	Isophorondiamine-isobutyraldimine	0.1-1		

Section 4 - FIRST AID MEASURES

Description of Necessary Measures

IF exposed or concerned: Get medical advice/attention.

Inhalation

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

Skin

Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

Eves

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Ingestion

If swallowed, get medical attention.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically and supportively.

Most Important Symptoms/Effects

Acute

Causes skin irritation. Causes serious eye irritation. May cause allergic skin reaction. May cause drowsiness or dizziness.

Delayed

May cause allergic skin reaction. Suspected of causing cancer. May cause liver and kidney damage.

Page 3 of 13 Issue date: 2018-10-09 Revision 1.0



Material Name: Low-VOC PVC Step 2 Primer SDS 10-3227

Note to Physicians Contains: toluene.

Section 5 - FIRE FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media

Dry chemical, foam or carbon dioxide. Water may be ineffective.

Unsuitable Extinguishing Media

Do not use high-pressure water streams.

Special Hazards Arising from the Chemical

Flammable liquid and vapor.

Hazardous Combustion Products

Oxides of carbon, oxides of nitrogen

Advice for firefighters

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

Fire Fighting Measures

Move container from fire area if it can be done without risk.

Section 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protective clothing and equipment, see Section 8.

Methods and Materials for Containment and Cleaning Up

Remove all sources of ignition. Avoid breathing vapors. Ventilate the area. Use non-sparking tools. Use clean non-sparking tools to collect absorbed material and place it into loosely-covered metal or plastic containers for later disposal. Large spills: Dike for later disposal. Prevent entry into waterways, sewers, basements, or confined areas.

Environmental Precautions

Avoid release to the environment. Collect spillage.

Section 7 - HANDLING AND STORAGE

Precautions for Safe Handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat and ignition sources. When using do not smoke. Use non-sparking tools. Ground any equipment used in handling. Wash with plenty of soap and water. Wash contaminated clothing before reuse. KEEP OUT OF REACH OF CHILDREN. Keep container tightly closed. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static

Page 4 of 13 Issue date: 2018-10-09 Revision 1.0



Material Name: Low-VOC PVC Step 2 Primer

SDS 10-3227

discharge. Do not breathe gas, fumes, vapor, or spray. Contaminated work clothing should not be allowed out of the workplace.

Conditions for Safe Storage, Including any Incompatibilities

Keep container tightly closed

Store in a well-ventilated place. Keep cool

Store locked up

Keep away from heat, sparks and flame. Do not cut, puncture, or weld on or near this container. Empty containers may contain product residue. Keep away from incompatible materials.

Incompatible Materials

Strong oxidizing agents, acids, bases

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Component Exposure Limits

Toluene	108-88-3					
ACGIH:	20 ppm TWA					
NIOSH:	100 ppm TWA; 375 mg/m3 TWA	150 ppm STEL; 560 mg/m3 STEL				
	500 ppm IDLH					
Europe:	50 ppm TWA; 192 mg/m3 TWA 100 ppm STEL; 384 mg/m3 STEL					
	Possibility of significant uptake through the skin					
OSHA (US):	200 ppm TWA 300 ppm Ceiling					
Mexico:	50 ppm TWA LMPE-PPT; 188 mg	/m3 TWA LMPE-PPT				
	Skin - potential for cutaneous absorption					
PCBTF	98-56-6					
ACGIH:	2.5 mg/m3 TWA as F (related to Fluorides)					
OSHA (US):	2.5 mg/m3 TWA as F; 2.5 mg/m3 TWA dust (related to Fluorides)					
Mexico:	2.5 mg/m3 TWA LMPE-PPT as F (related to Fluorides)					

Biological limit value

There are no biological limit values for any of this product's components.

Engineering Controls

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

Page 5 of 13 Issue date: 2018-10-09 Revision 1.0



Material Name: Low-VOC PVC Step 2 Primer SDS 10-3227

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear splash resistant safety goggles. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

Skin Protection

Wear appropriate chemical resistant clothing. Wear protective shoes.

Respiratory Protection

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Glove Recommendations

Wear appropriate chemical resistant gloves.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	thin brown liquid Physical State		liquid	
Odor	Naphthenic distillate Color		Light brown	
Odor Threshold	Not available	рН	Not available	
Melting Point	-9533 °C(-139 - 27°F) Boiling Point		111 - 139 °C(232 -282°F)	
Freezing point	Not available	Evaporation Rate	1.4	
Boiling Point Range	Not available	Flammability (solid, gas)	Not available	
Autoignition	246 °C(475°F)	Flash Point	4 °C(40°F)	
Lower Explosive Limit	0.9	Decomposition	Not available	
Upper Explosive Limit	10.5	Vapor Pressure	7.4 mmHg	
Vapor Density (air=1)	5.7	Specific Gravity (water=1)	Not available	
Water Solubility	insoluble	Partition coefficient: n- octanol/water	Not available	
Viscosity	<200 cps	Solubility (Other)	Not available	
Density	1.177	voc	<250 g/L	

Page 6 of 13 Issue date: 2018-10-09 Revision 1.0



Material Name: Low-VOC PVC Step 2 Primer

Section 10 - STABILITY AND REACTIVITY

SDS 10-3227

Reactivity

No reactivity hazard is expected.

Chemical Stability

Stable under normal conditions of use.

Possibility of Hazardous Reactions

Will not polymerize.

Conditions to Avoid

Keep away from heat/sparks/open flame/hot surfaces - No smoking. Take action to prevent static discharges. Avoid contact with incompatible materials.

Incompatible Materials

Strong oxidizing agents, acids, bases

Hazardous decomposition products

Oxides of carbon, oxides of nitrogen

Section 11 - TOXICOLOGICAL INFORMATION

Information on Likely Routes of Exposure

Inhalation

May cause drowsiness or dizziness.

Skin Contact

Causes skin irritation.

Eve Contact

Causes serious eye irritation.

Ingestion

No information on significant adverse effects.

Acute and Chronic Toxicity

Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Solvent naphtha, petroleum, light aliphatic (64742-89-8)

Oral LD50 Rat >2000 mg/kg Dermal LD50 Rat >2000 mg/kg Inhalation Rat >5000 ppm 1 hour

Isophorone Diisocyanate (Trade Secret)

Oral LD50 Rat >20000 mg/kg Dermal LD50 Rabbit 4000 mg/kg Inhalation LC50 Rat 5 mg/l 4 h

Issue date: 2018-10-09 Revision 1.0 Page 7 of 13



Material Name: Low-VOC PVC Step 2 Primer SDS 10-3227

Toluene (108-88-3)

Oral LD50 >7000 mg/kg Dermal LD50 12 - 14 g/kg Inhalation LC50 30 mg/L

chlorinated homopolymer (Trade Secret)

Oral Rat 5000 mg/kg

PCBTF (98-56-6)

Oral LD50 Rat 13 g/kg Dermal LD50 Rabbit >2 mL/kg Inhalation LC50 Rat 33 mg/L 4 h

Isophorondiamine-isobutyraldimine (Trade Secret)

Oral Rat 4150 mg/kg [OECD Test Guideline 401] Dermal Rat >5000 mg/kg [OECDTest Guideline 402]

Immediate Effects

Causes skin irritation. Causes serious eye irritation. May cause allergic skin reaction. May cause drowsiness or dizziness.

Delayed Effects

May cause allergic skin reaction. Suspected of causing cancer. May cause liver and kidney damage.

Irritation/Corrosivity Data

Causes skin and eye irritation.

Respiratory Sensitization

No information available for the product.

Dermal Sensitization

May cause allergic skin reaction.

Component Carcinogenicity

Toluene	108-88-3
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
IARC:	Monograph 71 [1999]; Monograph 47 [1989] (Group 3 (not classifiable))
PCBTF	98-56-6
ACGIH:	A4 - Not Classifiable as a Human Carcinogen (related to Fluorides)

Germ Cell Mutagenicity

No information available for the product.

Tumorigenic Data

No data available

Reproductive Toxicity

No information available for the product.

Page 8 of 13 Issue date: 2018-10-09 Revision 1.0



Material Name: Low-VOC PVC Step 2 Primer SDS 10-3227

Specific Target Organ Toxicity - Single Exposure central nervous system

Specific Target Organ Toxicity - Repeated Exposure

Prolonged exposure may cause liver and kidney damage.

Aspiration hazard

No information available for the product.

Medical Conditions Aggravated by Exposure

May cause allergic skin reaction.

Section 12 - ECOLOGICAL INFORMATION

Solvent naphtha, petroleum, light aliphatic	64742-89-8			
Algae:	EC50 72 h Pseudokirchneriella subcapitata 4700 mg/L IUCLID			
Isophorone Diisocyanate	Trade Secret			
Fish:	LC50 96 h Oncorhynchus mykiss 9.22 mg/L			
Invertebrate:	EC50 48 h Daphnia magna 6.14 mg/L IUCLID			
Toluene	108-88-3			
Fish:	LC50 96 h Pimephales promelas 15.22 - 19.05 mg/L [flow-through] (1 day old); LC50 96 h Pimephales promelas 12.6 mg/L [static]; LC50 96 h Oncorhynchus mykiss 5.89 - 7.81 mg/L [flow-through]; LC50 96 h Oncorhynchus mykiss 14.1 - 17.16 mg/L [static]; LC50 96 h Oncorhynchus mykiss 5.8 mg/L [semi-static]; LC50 96 h Lepomis macrochirus 11 - 15 mg/L [static]; LC50 96 h Oryzias latipes 54 mg/L [static]; LC50 96 h Poecilia reticulata 28.2 mg/L [semi-static]; LC50 96 h Poecilia reticulata 50.87 - 70.34 mg/L [static]			
Algae:	EC50 96 h Pseudokirchneriella subcapitata >433 mg/L IUCLID; EC50 72 h Pseudokirchneriella subcapitata 12.5 mg/L [static] EPA			
Invertebrate:	EC50 48 h Daphnia magna 5.46 - 9.83 mg/L [static] EPA; EC50 48 h Daphnia magna 11.5 mg/L IUCLID			

Page 9 of 13 Issue date: 2018-10-09 Revision 1.0



Material Name: Low-VOC PVC Step 2 Primer SDS 10-3227

PCBTF		98-56-6
Invertebrate:		EC50 48 h Daphnia magna 3.68 mg/L IUCLID

Section 13 - DISPOSAL CONSIDERATIONS

Disposal Methods

Dispose of contents/container in accordance with local/regional/national/international regulations. Subject to disposal regulations: U.S. EPA 40 CFR 262. Hazardous Waste Number(s): D001.

Section 14 - TRANSPORT INFORMATION

US DOT Information:

Shipping Name:ADHESIVES

Hazard Class: 3 UN/NA #: UN1133 Packing Group: II Required Label(s): 3

IATA Information:

Shipping Name:ADHESIVES

Hazard Class: 3 UN#: UN1133 Packing Group: II Required Label(s): 3

TDG Information:

Shipping Name:ADHESIVES

Hazard Class: 3 UN#: UN1133 Packing Group: II

Section 15 - REGULATORY INFORMATION

U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Toluene	108-88-3
SARA 313:	1 % de minimis concentration

Page 10 of 13 Issue date: 2018-10-09 Revision 1.0



Material Name: Low-VOC PVC Step 2 Primer

SDS 10-3227

CERCLA:	1000 lb final RQ; 454 kg final RQ
TSCA 12b:	Section 4, 1 % de minimus concentration (related to Hydrocarbons, C>4)
PCBTF	98-56-6
TSCA 12b:	Section 4, 1 % de minimus concentration

SARA Section 311/312 (40 CFR 370 Subparts B and C)

Acute Health: Yes Chronic Health: Yes Fire: Yes Pressure: No Reactivity: No

U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Toluene	108-88-3	Yes	Yes	Yes	Yes	Yes
PCBTF	98-56-6	Yes	No	Yes	Yes	Yes

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects

Toluene	108-88-3
Repro/Dev. Tox	developmental toxicity, 1/1/1991

Canadian WHMIS Ingredient Disclosure List (IDL)

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

Toluene	108-88-3
	1 %

Component Analysis - Inventory

Solvent naphtha, petroleum, light aliphatic (64742-89-8)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

Isophorone Diisocyanate (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

Page 11 of 13 Issue date: 2018-10-09 Revision 1.0



Material Name: Low-VOC PVC Step 2 Primer SDS 10-3227

Toluene (108-88-3)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

chlorinated homopolymer (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	No

PCBTF (98-56-6)

US	CA	EU	AU	РН	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	Yes	Yes	No	Yes	Yes	No

Isophorondiamine-isobutyraldimine (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	No	No	Yes	Yes	No

Section 16 - OTHER INFORMATION

HMIS Rating

Health: 2 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe * = Chronic hazard

NFPA Ratings

Health: 2 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

Summary of Changes New SDS: 4/24/2015

Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD -

Page 12 of 13 Issue date: 2018-10-09 Revision 1.0



Material Name: Low-VOC PVC Step 2 Primer SDS 10-3227

Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA -Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of LIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH -Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act: STEL - Short-term Exposure Limit: TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

Other Information

Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.

Page 13 of 13 Issue date: 2018-10-09 Revision 1.0