

## Material Name: Universal Single-Ply Sealant

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Material Name Universal Single-Ply Sealant

Trade Names Part Number(s): 310131, 342705

Synonyms Sealants

Chemical Family Sealants

**Product Use** Sealants

**Restrictions on Use** For industrial use only.

#### Manufacturer Information

Carlisle SynTec 1285 Ritner Highway Carlisle, PA 17013 USA Phone: +1-800-479-6832 Emergency Phone #: +1-800-424-9300 (CHEMTREC)

## **Supplier Information:**

Mule-Hide Products Co., Inc 1195 Prince Hall Dr. Beloit, WI 53511 USA Phone: 800-786-1492

# Section 2 - HAZARDS IDENTIFICATION

Classification in accordance with paragraph (d) of 29 CFR 1910.1200.Physical HazardsNot classified

Health HazardsSkin sensitization – Category 1BSerious eye damage/irritation – Category 2A

**Environmental Hazards** Not Classified Specific Target Organ Toxicity - Repeated Exposure - Category 1 (lungs)

## **GHS Label Elements**

Symbol(s)





# Material Name: Universal Single-Ply Sealant

Signal Word Warning

# Hazard Statement(s)

May cause an allergic skin reaction Causes serious eye irritation

## **Precautionary Statement(s)**

# Prevention

Avoid breathing vapors Contaminated work clothing must not be allowed out of the workplace Wash hands thoroughly after handling Wear protective gloves and eye protection Wash contaminated clothing before reuse

# Response

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice If on skin: Wash with plenty of water and soap If skin irritation or rash occurs: Get medical advice

# Storage

None requires

# Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations

# Contains

N-(3-(trimethoxysilyl)propyl)ethylenediamine, trimethoxyvinylsilane, dioctyltinbis(acetylacetonate).

# **Other Hazards**

None known.

# Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Substance either with health hazards present above their cut-off values/concentration limits or which may present a health risk below their applicable cut-off value:

CAS	Component Name	Percent
1760-24-3	N-(3-(trimethoxysilyl)propyl]ethylenediamine	< 3
2768-02-7	Trimethoxyvinylsilane	< 3
54068-28-9	Dioctyltinbis(acetylacetonate)	< 1



#### Material Name: Universal Single-Ply Sealant

# Section 4 - FIRST AID MEASURES

#### **Description of Necessary First-Aid Measures**

#### **General advice**

In all cases of doubt, or if symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.

#### Inhalation

If inhalation causes adverse effects, remove to fresh air.

#### Skin

Wash skin thoroughly with soap and water. Get medical advice if skin irritation or rash occurs. In the event of any sensitization symptoms developing, ensure further exposure is avoided.

#### Eyes

Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical advice if eye irritation persists.

#### Ingestion

Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. DO NOT induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.

#### Indication of any immediate medical attention and special treatment needed

Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

## Most Important Symptoms/Effects

# Inhalation No specific symptoms known. Ingestion

May cause discomfort if swallowed.

Skin contact

Allergic rash.

Eye contact

Causes serious eye irritation.

**Note to Physicians** Treat symptomatically.

# Section 5 - FIRE FIGHTING MEASURES

#### Extinguishing Media Suitable Extinguishing Media

Water spray, fog or mist. Foam, carbon dioxide or dry powder.



# Material Name: Universal Single-Ply Sealant

Unsuitable Extinguishing Media

Do not use water jet as an extinguisher, as this will spread the fire.

# Special Hazards Arising from the Substance or Mixture

# Specific Hazard

Oxides of carbon. Oxides of nitrogen. No usual fire or explosion hazards noted.

#### **Hazardous Combustion Products**

Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

#### Advice for firefighters

No specific firefighting precautions known.

#### **Fire Fighting Measures**

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

# Section 6 - ACCIDENTAL RELEASE MEASURES

## Personal Precautions, Protective Equipment and Emergency Procedures

Wear appropriate protective clothing. Avoid contact with eyes and skin.

#### **Environmental Precautions**

Do not discharge into drains or watercourses or onto the ground.

## Methods and Materials for Containment and Cleaning Up

Collect and place in suitable waste disposal containers and seal securely. Clean any slippery coating that remains using a detergent/soap solution or other biodegradable cleaner.

#### **Environmental Precautions**

For personal protection, see Section 8. See Section 11 for additional information on health hazards. For waste disposal, see section 13.

Section 7 - HANDLING AND STORAGE

#### **Precautions for Safe Handling**

Avoid spilling. Avoid contact with skin and eyes. Persons susceptible to allergic reactions should not handle this product. Good personal hygiene procedures should be implemented.

# Conditions for Safe Storage, Including any Incompatibilities

#### Technical measures and Storage Conditions

Store in tightly-closed, original container in a dry, cool and well-ventilated place.

## **Requirements for Storage Areas**

Store in original container.

# Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

SDS 10-2105



# Material Name: Universal Single-Ply Sealant

#### **Component Parameters**

Occupational exposure limits:

Tin, organic compounds (as Sn): OSHA PEL (8-hour TWA): 0.1 mg/m3 NIOSH REL (Up to 10-hour TWA): 0.1 mg/m3 ACGIH 2019 TLV (8-hour TWA): 0.1 mg/m3 ; ST (15-minute STEL): 0.2 mg/m3 (Skin – potential for cutaneous absorption)

#### **Exposure Controls**

Appropriate engineering controls: No specific ventilation requirements.

#### **Personal Protective Equipment**



#### **Eye/face protection**

Wear eye protection. Personal protective equipment for eye and face protection should comply with appropriate standards such as NIOSH (US) or EN 166 (EU).

#### **Hand Protection**

Use protective gloves. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. Protective gloves should comply with appropriate standards such as NIOSH (US) or EN 374 (EU).

#### Skin and Body Protection

Wear appropriate clothing to prevent repeated or prolonged skin contact.

#### **Hygiene Measures**

Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated.

#### **Respiratory Protection**

No specific recommendations.

Appearance	Paste	Color	Dark Blue, Gray
Odor	Mild	Odor Threshold	Not available
рН	Not available	Melting Point	Not available
Initial Boiling Point and Range	Not available	Flash Point	Not available
<b>Evaporation Rate</b>	Not available	Flammability	Not available

# Section 9 - PHYSICAL AND CHEMICAL PROPERTIES



# Material Name: Universal Single-Ply Sealant

SDS 10-2105

Upper/lower Flammability or Explosive Limits	Not available	Vapor Pressure	Not available
Vapor Density	Not available	Relative Density	1.44 – 1.54 @ 20°C
Solubility(ies)	Insoluble in water	Partition coefficient: n- octanol/water	Not available
Auto-ignition Temperature	Not applicable	Viscosity	6,000 – 10,000 P @ 20°C
<b>Explosive Properties</b>	Not applicable	VOC's	< 10 grams/liter
Oxidising Properties	The mixture itself has not been tested but none of the ingredient substances meet the criteria for classification as oxidizing.		

# Section 10 - STABILITY AND REACTIVITY

#### Reactivity

There are no known reactivity hazards associated with this product.

#### **Chemical Stability**

Stable at normal ambient temperatures and when used as recommended.

## **Possibility of Hazardous Reactions**

Not known. Will not polymerise.

## **Conditions to Avoid**

Avoid excessive heat for prolonged periods of team.

## **Incompatible Materials**

No specific material or group of materials is likely to react with the product to produce a hazardous situation.

## Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Oxides of nitrogen

Section 11 - TOXICOLOGICAL INFORMATION		
Acute toxicity - oral: Trimethoxyvinylsilane: N-(3-(trimethoxysilyl)propyl-	Not classified based on available information. LD50 > 7120 mg/kg (rat, OECD 401).	
ethylenediamine:	LD50 > 2295 mg/kg (rat, EPA OPPTS 870.1100).	
Acute toxicity – dermal: Trimethoxyvinylsilane: N-(3-(trimethoxysilyl)propyl-	Not classified based on available information. LD50 > 2000 mg/kg (rabbit, OECD 402).	



## Material Name: Universal Single-Ply Sealant

SDS 10-2105

ethyle	enediamine:	LD50: 6899 mg/kg (rabbit, EPA OPPTS 870.1200).
Acute toxicity – inhalation: Trimethoxyvinylsilane: N-(3-(trimethoxysilyl)propyl- ethylenediamine:	Not classified based on available information. LC50: 16.8 mg/L (rat, vapor, 4 hours, OECD 403).	
	LC50: 1.49 – 2.44 mg/L (rat, mist, 4 hours, OECD 403).	
Skin	corrosion/irritation:	Not classified based on available information.
Serious eye damage/irritation: N-(3-(trimethoxysilyl)propyl- ethylenediamine:	Classified as Eye Irritant Category 2A.	
	Causes serious eye damage (rabbit, OECD 405).	
Respi	iratory sensitization:	Not classified based on available information.
Trime	sensitization: ethoxyvinylsilane: (trimethoxysilyl)propyl-	Classified as Skin Sensitizer Category 1B. Sensitizing (Buehler test (OECD 406)).
ethylenediamine:		Sensitizing (Guinea pig maximisation test (OECD 406)).
Germ	cell mutagenicity:	Not classified based on available information.
Carci	nogenicity:	This product is not considered to be a carcinogen by IARC, NTP, or OSHA.
IARC Monographs. Overall Evaluation of Carcinogenicity: Not listed.		

IARC Monographs. Overall Evaluation of Carcinogenicity: Not listed. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052): Not regulated. U.S. National Toxicology Program (NTP) Report on Carcinogens: Not listed.

7.611	logue data: 2024 05 22	
Eye contact:	Causes serious eye irritation.	
Skin contact:	May cause sensitization by skin contact.	
Ingestion:	May cause discomfort if swallowed.	
Information on Likely Routes of ExposureInhalation:No specific health hazards known.		
Aspiration hazard:	Not relevant, due to the form of the product.	
Specific target organ toxicity – repeated exposure:	Not classified based on available information.	
Specific target organ toxicity – single exposure:	Not classified based on available information.	
Reproductive toxicity:	Not classified based on available information.	



#### Material Name: Universal Single-Ply Sealant

Delayed and immediate effects: Causes serious eye irritation and may cause an allergic skin reaction.

Acute and chronic health hazards: Causes serious eye irritation and may cause an allergic skin Reaction.

Section 12 - ECOLOGICAL INFORMATION

#### **Ecotoxicity**

There are no data available for the product. In cross-linked state, the product is not soluble in water and is easily separable from water by filtration.

#### **Component Analysis - Aquatic Toxicity**

Not classified based on available information.

Trimethoxyvinylsilane		2768-02-7
Fish: LC50, 9		hours: 191 mg/l, Oncorhynchus mykiss
Invertebrates: EC:		hours: 168.7 mg/l, Daphnia magna
Plants:	EC50, 72	hours > 89 mg/l, Pseudokirchneriella subcapitata
N-(3-(trimethoxysilyl)propylethylenedia	nine	1760-24-3
Fish:	LC50, 96	hours: 597 mg/l, Brachydanio rerio (Zebra Fish)
Invertebrates:	EC50, 48	hours: 81 mg/l, Daphnia magna
Plants:	EC50, 96 hours: 8.8 mg/l, Pseudokirchneriella subcapitata	

#### Persistence and Degradability

This product is not expected to be readily biodegradable.

#### **Bioaccumulative Potential**

Bioaccumulation is unlikely to be significant because of the low water-solubility of this product.

#### Mobility

The product is insoluble in water.

#### **Results of PBT and vPvB Assessment**

The product does not contain any substances classified as PBT or vPvB.

#### Other Adverse Effects None known.



#### Material Name: Universal Single-Ply Sealant

Section 13 - DISPOSAL CONSIDERATIONS

# **General Information**

Waste is classified as hazardous waste. Dispose of contents/container in accordance with local, state and federal regulations.

#### **Disposal Methods**

Collect and place in suitable waste disposal containers and seal securely.

Section 14 - TRANSPORT INFORMATION

US DOT Information: UN/NA #: Not regulated

#### IATA Information: UN#: Not regulated

UN#. Not regulated

# **IMDG Information:**

UN#: Not regulated

# Section 15 - REGULATORY INFORMATION

## **U.S. Federal Regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

CERCLA Hazardous Substance List (40 CFR 302.4): Not listed.

SARA Section 302 Extremely hazardous substances (40 CFR 355): Not listed.

SARA Section 313 Toxic Release Inventory Chemicals (40 CFR 372.65): Not listed.

SARA Section 311/312 (40 CFR 370 Subparts B and C) hazard categories: Health hazards (skin sensitization and serious eye irritation); Physical hazards: No.

## **Other Federal Regulations**

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List: Not listed. Clean Air Act (CAA) Section 112(r) List of Substances for Accidental Release Prevention (40 CFR 68.130): Not listed. Clean Water Act Toxic Pollutants List (40 CFR 401.15) and Priority Pollutants List (40 CFR 423 Appendix A): Not listed.

## **U.S. State Regulations**

Massachusetts Right to Know Hazardous Substance List: Not listed. New Jersey Right to Know Hazardous Substances List: Not listed. Pennsylvania Right to Know Hazardous Substances List: Not listed.



# Material Name: Universal Single-Ply Sealant

US. California Proposition 65 California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

# **Toxic Substances Control Act**

**(TSCA) Inventory:** One or more components of the product are either not listed or are exempt from listing on the inventory.

# Section 16 - OTHER INFORMATION

#### **Summary of Changes**

Revision Date: May 23, 2024 Revision Note: General Update

## Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations: DFG - Deutsche Forschungsgemeinschaft: DOT - Department of Transportation: DSD -Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA -Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List OfLIsts™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH -Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

#### **Other Information**

## **Disclaimer:**

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, CCWI Company must rely upon the hazard evaluation of such components submitted by that product's manufacturer or importer. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein



## Material Name: Universal Single-Ply Sealant

may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.