

## **Mule-Hide Products - Miscellaneous Videos**

### **Silicone Roof Coatings**

**115 Cleaner:** Mule-Hide 115 Cleaner is used as a general purpose cleaner prior to the coating of approved surfaces with Mule-Hide Coatings Systems. Power washing with 115 Cleaner effectively removes existing oil, dirt, or grease that would adversely affect the bonding of new coatings, and prepares those surfaces for the new primer/coating.

**Si Cleaning Solvent:** Mule-Hide Si Cleaning Solvent is a high flash aromatic solvent that may be used to clean tools and equipment. This product is suitable for cleanup of asphalt, thermoplastic and silicone based roofing products.

**100% Silicone Roof Coating:** Mule-Hide 100% Silicone Roof Coating is a 100% silicone based, single part roof coating that creates a barrier that is resistant to weathering, is durable, breathable, watertight and weatherproof.

**Silicone Sealant:** Mule-Hide Products offers a single-part roof repair mastic that creates a barrier that is resistant to natural weathering. Mule-Hide 100% Silicone Sealant can be applied over spray applied polyurethane foam, EPDM, aged PVC, concrete, asphalt BUR, granulated modified bitumen and metal roofs. May be applied to TPO roofs with Mule-Hide Si TPO Primer.

**100% Silicone Skylight Coating:** Mule-Hide 100% Silicone Skylight Coating is a single part roof coating manufactured from durable inorganic silicone elastomers, reinforcing pigments and silane adhesions promoters. 100% Silicone Skylight Coating is a oxime neutral cure chemistry that is not corrosive to metals.

**Si TPO Primer:** Mule-Hide Si TPO Primer is a primer used to promote adhesion with our Mule-Hide 100% Silicone Roof Coating to new and aged TPO roofing membranes. Si TPO Primer is manufactured from a fast evaporating solvent carries and adhesive resins. Primer has a blue tint to allow applicator to better gauge application rates.

**Si 2-Part Epoxy Primer:** Si 2-Part Epoxy Primer is a water-based primer used to promote adhesion and prevent asphalt staining with our Mule-Hide 100% Silicone Roof Coating. Also used over areas of rusted metal to encapsulate rust. Mule-Hide Si 2-Part Epoxy Primer is not intended for exposure to the elements and must be top coated with Mule-Hide 100% Silicone Roof Coating within five days of application. Do not allow Si 2-Part Epoxy Primer to freeze.

## **Mortar Sentry Water Seal**

**Mortar Sentry**: Mortar Sentry Water Seal is designed for use on brick, mortar, concrete block, cultured stone, sandstone and concrete. It is not recommended for use on non-silicate natural stone such as limestone or dolomite. Mortar Sentry is a silane/siloxane based waterproofing treatment consisting of two products. Mortar Sentry Water Seal 10 is a 10% active solution and is recommended for vertical surfaces. Mortar Sentry Water Seal 15 is a 15% active solution and is recommended for horizontal surfaces.