# Fleece Back Recovery System

Understanding the Benefits

The Right Choice for Low-Slope Roofing Products 800-786-1492 • mulehide.com

# **Direct Application Permitted**


- No cover board required over approved substrates
- Existing Aged Single-Ply (EPDM, TPO Hypalon)<sup>1,2</sup>
- Existing Modified Asphalt System

# Aesthetics

• Fleece backing significantly helps to protect from asphalt staining when membrane is installed directly over Modified Asphalt Systems<sup>1,3</sup>

# **Puncture and Hail Resistance**

• Up to 50% superior puncture resistance compared to smooth back single-ply membranes



Adhered Fleece back Recovers

Fleece back (TPO, PVC or PVC KEE HP) Membrane Helix Max Low-Rise Adhesive (6" o.c. beads or splatter application) Existing aged Single-ply<sup>1,2</sup> (EPDM, TPO Hypalon), or existing modified asphalt system<sup>1,3</sup>

- Existing Roof Insulation
- Existing Roof Deck

#### Difficult or Problematic Decks to Fasten to

Adhered Fleece back recovers eliminate not only cost of cover board,<sup>1, 2, 3</sup> but also more expensive an labor intensive fasteners and plates associated with decks such as concrete, cementitious wood fiber and gypsum.

#### **Regulation Friendly**

2-part urethane adhesive (Helix Max) is VOC and HFC free - perfect for states where regulations are in place.

#### **Minimal Owner Distrubance**

Helix Max Adhesive application is quiet and have very low odor.

| Calculate Cost Savings vs. Traditional Adhered Recover |                                      |
|--|--------------------------------------|
| Traditional Adhered Recover                            | Fleece Back Adhered Recover          |
| ✓ Cover board  | Cover board (not required)           |
| ✓ Fasteners & plates to secure cover board             | ✗ Fasteners & Plates (not required)  |
| ✓ Smooth backed membrane adhesive                      | ✓ Helix Max 2-part urethane adhesive |
| <ul> <li>Smooth backed membrane</li> </ul>             | ✓ Fleece back membrane               |

<sup>&</sup>lt;sup>1</sup>Contact Mule-Hide for specific requirements on direct recover applications. <sup>2</sup>Not acceptable over existing PVC or KEE roof membrane.

Existing smooth surface BUR (Type III or IV Asphalt), smooth surface modified-bitumen or mineral surface cap sheet. Not permitted if existing modified asphalt system is aluminum coated.




Rugged • Time-Tested • Weather-Tested





# Fleece Back Recovery System

### Mechanically-Attached Fleece back Recovers



Fleece back (TPO, PVC or PVC KEE HP) Membrane Existing aged Single-ply (EPDM, TPO Hypalon)<sup>1,2</sup> or existing modified asphalt system<sup>1,3</sup>

Existing Roof Insulation
 Existing Roof Deck (Plywood or Metal)

Mechanically-Attached Fleece back recovers are most ideal over steel or wood roof decks that achieve proper pullout values - Mechanically attaching the Fleece back membrane directly over substrate<sup>1,2,3</sup> can eliminate the cost and laborassociated with both cover boards and adhesives.

| Calculate Cost Savings vs. Traditional Adhered Recover |  |
|--|--|
| Traditional Mechanically Attached<br>Recover           | Traditional Fleece Back<br>Mechanically Attached Recover |
| ✓ Cover board  | X Cover board (not required)                             |
| ✓ Fasteners & plates to secure cover board             | ✗ Fasteners & Plates (not required)                      |
| <ul> <li>Smooth backed membrane</li> </ul>             | ✓ Fleece back membrane                                   |

# NDL (No Dollar-Limit warranties available)

6

- Available on Commercial Only (Contact Mule-Hide for terms and limitiations)
- Covers labor and materials, and is not limited to the original installed cost.
- Must be installed by a Mule-Hide warranty eligible applicator
- Requires inspection by a Mule-Hide technical representative

#### **Residential Material Only Warranties Available**



<sup>1</sup>Contact Mule-Hide for specific requirements on direct recover applications. <sup>1</sup>Not acceptable over existing PVC or KEE roof membrane. <sup>3</sup>Existing smooth surface BUR (Type III or IV Asphalt), smooth surface modified-bitumen or mineral surface cap sheet. Not permitted if existing modified asphalt system is aluminum coated.

The information herein should not be considered all-inclusive and should always be accompanied by a review of the Mule-Hide specifications and guidelines and good application practices.

This information herein is based upon data and knowledge considered to be true and accurate at the time of printing and is provided for the reader's consideration, investigation and verification. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Mule-Hide Products Co., Inc. does not warrant any results to be obtained. Statements concerning possible use of Mule-Hide products are made without knowledge of your particular roof and such an application may not be fit for your particular purpose. MULE-HIDE DISCLAIMS ALL WARRANTIES, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, except written warranties attached to Mule-Hide products and written warranties signed by an officer of Mule-Hide.

Visit the Mule-Hide website at www.mulehide.com prior to any installation for updated technical specifications and details. Mule-Hide is a U.S. registered trademark. All rights reserved. REV 0 9/24