

#311 Non-Fibrated Emulsion Roof Coating

The Right Choice for Low-Slope Roofing Products

800-786-1492 • mulehide.com



Rugged • Time-Tested • Weather-Tested

Product Description

MuleHide #311 Non-Fibrated Emulsion Roof Coating stands up to heat, rain and snow and is particularly at home in hot climates. The asphalt-based clay emulsion roof coating protects smooth-surfaced asphalt built-up roofs and modified bitumen roofing membranes. It does not flow when applied in thick coats. When dry, it stays firmly in place, even when exposed to elevated temperatures.

- Good when used as a base coat prior to application of aluminum or elastomeric coatings.
- Effective as a base coat for reflective coatings.
- Also protects metal roofing, masonry, stucco, parapet walls, curbs, and base flashings.
- Effective in damp-proofing below-grade walls.
- Can be used as a protective coating on the inside of planter boxes.

Features & Benefits

- Environmentally friendly. MuleHide #311 Non-Fibrated Emulsion Roof Coating is water-based, solvent-free, and non-combustible. No "red tag" label for fire hazard is required.
- Contains a soft, ductile type of asphalt that makes it highly resistant to rain, snow and heat.
- The heavy-bodied, semi-paste consistency makes it easy to apply with a brush, roller, or sprayer.
- Great bonding strength.
- Exceptional durability and performance over a wide range of challenging temperatures and weather conditions. Will not mud crack and will remain highly resilient and durable through all seasons.
- Does not damage conventional asphalt-based roofing membranes.



Packaging: 4.7 Gallon Pail

Application Methods:



Code Approvals/Compliance:



Miami Dade County Product Control Approved



D1227 Type III Class I

Physical Property Information	
Property	Value
Maximum VOC	30 G/L
Consistency	Water Soluble
Flash Point (T.C.C)	None
Boiling Point	212° F
Vapor Density	Heavier Than Air

#311 Non-Fibrated Emulsion Roof Coating

Frequently Asked Questions

1. What criteria should contractors use when deciding whether to use MuleHide #311 Non-Fibrated Emulsion Roof Coating or MuleHide #301 Fibrated Emulsion Roof Coating?

MuleHide #311 Non-Fibrated Emulsion Roof Coating provides a smooth finish and glide-feel upon applying the product. Performance features and benefits between the #311 and #301 are very comparable, with the main difference being the texture and feel of the product.

2. What are the coverage rate and spray tip sizes for MuleHide #311 Non-Fibrated Emulsion Roof Coating?

The coverage rate for MuleHide #311 Non-Fibrated Emulsion Roof Coating is approximately 3 to 4 gallons per 100 sq. ft., depending on the roof surface. The spray requirements are 3,000 psi at 2 to 8 gallons per minute. Tip size = 0.0861<, Fan = 6 inches to 12 inches. (All values are approximate and may vary with ambient temperature and job conditions.)

3. How is MuleHide #311 Non-Fibrated Emulsion Roof Coating applied?

MuleHide #311 Non-Fibrated Emulsion Roof Coating can be applied using a roofing brush, a roller, or a high-pressure sprayer.

4. What is the drying time for MuleHide #311 Non-Fibrated Emulsion Roof Coating?

The drying time for MuleHide #311 Non-Fibrated Emulsion Roof Coating is 6 to 24 hours under good conditions, or 2 to 7 days during damp or cool weather. Actual drying time will vary depending on the specific weather conditions at the jobsite.

5. What is the shelf life of MuleHide #311 Non-Fibrated Emulsion Roof Coating?

With proper storage, the shelf life of MuleHide #311 Non-Fibrated Emulsion Roof Coating is 18 months from the date of manufacture.

6. At what temperature should MuleHide #311 Non-Fibrated Emulsion Roof Coating be stored?

MuleHide #311 Non-Fibrated Emulsion Roof Coating should be stored at a temperature of at least 45°F but not above 120°F. It should be stored at room temperature for at least 24 hours prior to use.

7. In what weather conditions can MuleHide #311 Non-Fibrated Emulsion Roof Coating be applied?

MuleHide #311 Non-Fibrated Emulsion Roof Coating should only be applied when the ambient temperature is at least 50°F and rising. Cold weather can result in uneven application and improper curing, and it will cause the product to stiffen, making application more difficult. Do not apply MuleHide #311 Non-Fibrated Emulsion Roof Coating if there is a threat of rain within 24 hours of application.



MuleHide #311 Non-Fibrated Emulsion Roof Coating being applied with a roller.

The information herein should not be considered all-inclusive and should always be accompanied by a review of the MuleHide specifications and guidelines and good application practices.

This information herein is based upon data and knowledge considered to be true and accurate at the time of printing and is provided for the reader's consideration, investigation and verification. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. ("MuleHide"). MuleHide does not warrant any results to be obtained. Statements concerning possible use of MuleHide products are made without knowledge of your particular roof and such an application may not be fit for your particular purpose. MULEHIDE DISCLAIMS ALL WARRANTIES, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, except written warranties attached to MuleHide products and written warranties signed by an officer of MuleHide.

Visit the MuleHide website at www.mulehide.com prior to any installation for updated technical specifications and details. MuleHide is a U.S. registered trademark. All rights reserved. REV 1 12/24