

MP Liquid Sealant

Roofing Sealant



The Right Choice for Low-Slope Roofing Products

800-786-1492 • mulehide.com

Rugged • Time-Tested • Weather-Tested

Product Description

MP Liquid Sealant is a single-component, non-shrink, advanced-technology sealant designed for filling pitch pans and sealing seams, endlaps, fasteners and flashings on metal roof systems prior to applying acrylic coatings.

It may be used in conjunction with ShapeShift™ straight and corner sections which can be combined to produce pitch pans of various sizes and shapes. It has adequate viscosity to avoid running on steep slope application and drain out issues that are encountered with less viscous sealers. MP Liquid Sealant is 100% solids which results in zero shrinkage. Temperature performance range is -40° F to +200° F.

Features & Benefits

- 100% solids will not shrink
- One-part sealer seals seams and fasteners, gutters and roof projections
- No primer is required on the inside surfaces of the pan
- Short cut-off string during application
- Tack-free with excellent cure times
- Flexible in low temperatures

Used as a component within these systems:



MORE INFO



Applying to a pitch pan.

Packaging:

- 2 Liter Pouch (4/3.5 G Bucket)
- Available in white, black or gray

Code Approvals/Compliance:

- ASTM C-920, Type S, Grade P, Class 25 use T and M
- Fed Spec TT-S-00230c, Class A, Type I
- CAN/CGSB-19.13-M87, Class C-1-40-B-N and C-1-25-B-N

The information herein should not be considered all-inclusive and should always be accompanied by a review of the MuleHide specifications and guidelines and good application practices.

This information herein is based upon data and knowledge considered to be true and accurate at the time of printing and is provided for the reader's consideration, investigation and verification. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. ("MuleHide"). MuleHide does not warrant any results to be obtained. Statements concerning possible use of MuleHide products are made without knowledge of your particular roof and such an application may not be fit for your particular purpose. MULEHIDE DISCLAIMS ALL WARRANTIES, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, except written warranties attached to MuleHide products and written warranties signed by an officer of MuleHide.

Visit the MuleHide website at www.mulehide.com prior to any installation for updated technical specifications and details. MuleHide is a U.S. registered trademark. All rights reserved. REV 4 7/26