

SA-APP KoolCap®

Highly-Reflective Self-Adhering Membrane



The Right Choice for Low-Slope Roofing Products

800-786-1492 • mulehide.com

Rugged • Time-Tested • Weather-Tested

SA-APP KOOLCAP® AND SA-APP KOOLCAP® FR

A highly reflective, self-adhered APP modified bitumen roofing membrane manufactured using Adeso® dual-compound technology, whereby the membrane consists of an APP (atactic polypropylene) modified asphalt compound on top and a pressure sensitive adhesive compound on the bottom. SA-APP KoolCap® & SA-APP KoolCap® FR features CURE Technology®, an innovative thin film technology attributing to exceptional granule retention, stain and discoloration resistance and UV stabilization for long-term durability and performance. CURE is solvent-free and environmentally friendly. SA-APP KoolCap® & SA-APP KoolCap® FR have a highly reflective granule surface which meets or exceeds most standards for “Cool Roofing” and has a SRI of 96.

Constructed with premium APP resins and incorporating superior polyester reinforcing, SA-APP KoolCap® & SA-APP KoolCap® FR provides an exceptionally durable roofing product with exceptional tensile strength and dimensional stability. SA-APP KoolCap® & SA-APP KoolCap® FR features SEALLap® ULTRA side lap with self-adhesive compound for an instant bond, tested stronger than all other application methods and FASTLap®, granule free end lap. Each of these patented features provide for greater ease of application as well as improved long-term performance. SA-APP KoolCap® & SA-APP KoolCap® FR is also used as a flashing membrane in all applicable specifications.

BASIC USES

SA-APP KoolCap® & SA-APP KoolCap® FR membranes are designed for applications where the use of hot asphalt, cold process adhesive, or a propane torch is undesirable. Applications include new roofing, recover (retrofit) and BUR repairs. This system must be installed over an acceptable base sheet, roof insulation, or other suitable substrate. See the Mule-Hide Self-Adhered Modified Bitumen Application Guidelines for complete specifications and details.



SA-APP KOOLCAP®					
Product Code	Description	Thickness	Coverage	Weight	Carton
06MHSAAKC	32' 10" x 39-3/8" (10m x 1m)	4.0mm (160mils)	100 ft²	90 lbs.	1 Sq. Roll

SA-APP KOOLCAP® FR					
Product Code	Description	Thickness	Coverage	Weight	Carton
06MHSAAFKC	32' 10" x 39-3/8" (10m x 1m)	4.0mm (160mils)	100 ft²	90 lbs.	1 Sq. Roll

Various code approvals are available including: Factory Mutual, Underwriters Laboratories, Miami-Dade, Florida Product Approval, ICC-ESR and Texas Department of Insurance. Contact Mule-Hide Technical Department for specific ratings.



D6222 TYPE I

The information herein should not be considered all-inclusive and should always be accompanied by a review of the Mule-Hide specifications and guidelines and good application practices.

This information herein is based upon data and knowledge considered to be true and accurate at the time of printing and is provided for the reader's consideration, investigation and verification. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Mule-Hide Products Co., Inc. does not warrant any results to be obtained. Statements concerning possible use of Mule-Hide products are made without knowledge of your particular roof and such an application may not be fit for your particular purpose. MULE-HIDE DISCLAIMS ALL WARRANTIES, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, except written warranties attached to Mule-Hide products and written warranties signed by an officer of Mule-Hide.

Visit the Mule-Hide website at www.mulehide.com prior to any installation for updated technical specifications and details. Mule-Hide is a U.S. registered trademark. All rights reserved. REV 0 3/22