

# SA Base Sheet

## Self-Adhering Membrane



The Right Choice for Low-Slope Roofing Products

800-786-1492 • mulehide.com

Rugged • Time-Tested • Weather-Tested

### SA BASE SHEET & SA BASE SHEET FR

A premium self-adhered, fiberglass reinforced, modified bitumen membrane (with fire retardant additives)\* manufactured to meet the toughest code requirements of the industry. SA Base Sheet & SA Base Sheet FR are manufactured using Adeso® dual-compound technology, where the membrane consists of Styrene Butadiene Styrene (SBS) modified asphalt compound on top and a pressure sensitive adhesive compound on the bottom. The adhesive is covered with a split release liner. SA Base Sheet & Base Sheet FR are finished with a polyolefin film with printed lay lines on the top surface.

#### BASIC USES

SA Base Sheet & Base Sheet FR membranes are designed for applications where the use of hot asphalt, cold process adhesive, or a propane torch is undesirable. Applications include new roofing, recover (retrofit) and BUR repairs. SA Base Sheet & Base Sheet FR can be used as a waterproofing base sheet applied to approved roof decks or substrates. See the MuleHide Self-Adhered Modified Bitumen Application Guidelines for complete specifications and details.

#### PRODUCT BENEFITS

- Pre-applied adhesive on the back of the sheet.
- Durable - high performance reinforcement mat.
- No hot asphalt, fumes or flames required for installation.
- Excellent long term adhesion to multiple substrates and to base plies.
- Offers low-temp flexibility, puncture and tear resistance.
- Top film surface allows torching or self-adhering approved cap sheets\*

\*SA Base Sheet FR only

MORE INFO



SA BASE SHEET					
Product Code	Description	Thickness	Coverage	Weight	Carton
06MHSAB	65' 8" x 39-3/8" (20m x 1m)	2.0mm (80mils)	200 ft <sup>2</sup>	95 lbs.	2 Sq. Roll

SA BASE SHEET FR					
Product Code	Description	Thickness	Coverage	Weight	Carton
06MHSABF	65' 8" x 39-3/8" (20m x 1m)	2.0mm (80mils)	200 ft <sup>2</sup>	94 lbs.	2 Sq. Roll

**Various code approvals are available including:** Factory Mutual, Underwriters Laboratories, Miami-Dade, Florida Product Approval, ICC-ESR and Texas Department of Insurance. Contact MuleHide Technical Department for specific ratings.



D6163 TYPE I, GRADE S  
D1970

The information herein should not be considered all-inclusive and should always be accompanied by a review of the MuleHide specifications and guidelines and good application practices.

This information herein is based upon data and knowledge considered to be true and accurate at the time of printing and is provided for the reader's consideration, investigation and verification. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. ("MuleHide"). MuleHide does not warrant any results to be obtained. Statements concerning possible use of MuleHide products are made without knowledge of your particular roof and such an application may not be fit for your particular purpose. MULEHIDE DISCLAIMS ALL WARRANTIES, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, except written warranties attached to MuleHide products and written warranties signed by an officer of MuleHide.

Visit the MuleHide website at [www.mulehide.com](http://www.mulehide.com) prior to any installation for updated technical specifications and details. MuleHide is a U.S. registered trademark. All rights reserved. REV 1 12/24