

SPF+ 2.8 HFO

Spray Polyurethane Foam Part B



The Right Choice for Low-Slope Roofing Products

800-786-1492 • mulehide.com

Rugged • Time-Tested • Weather-Tested

Product Description

SPF+ 2.8 HFO is a sprayed-in-place, nominal 60 psi compressive strength, rigid, HFO-blown, closed-cell spray polyurethane foam (SPF) roofing system. This two-component SPF consists of SPF+ 2.8 HFO B component resin and SPF ISO A component. SPF+ 2.8 HFO provides an R-value of 6.7 per inch and a continuous insulation without thermal breaks. SPF+ 2.8 HFO roofing systems provide excellent wind uplift resistance, are self-flashing, seamless, and the closed-cell nature provides a durable, leak-resistant roofing system.

Features & Benefits

- Closed-cell SPF provides a fully adhered, monolithic, sustainable air barrier and thermal insulation for the roof
- Superior yield reduces cost and amount of material required
- Enhances wind uplift resistance
- Yields a smooth surface, reducing the need for extra coating
- Excellent adhesion to most surfaces
- Self-flashing, seamless application
- HFO-blown low global warming potential (LGWP)



Packaging:

- 55 Gallon Drum
- SPF ISO A component
- SPF+ 2.8 HFO B component resin

Application Methods:



Codes & Approvals:



SPF+ 2.8 HFO Series SPF Reactivity Grades

SPF+ 2.8 HFO Reactivities	Recommended Ambient Temp Range
SPF+ 2.8 HFO VS (Very Slow)	100°-125°F (38°-52°C)
SPF+ 2.8 HFO S (Slow)	85°-110°F (29.5°-43°C)
SPF+ 2.8 HFO R (Regular)	65°-90°F (18°-32°C)
SPF+ 2.8 HFO F (Fast)	50°-75°F (10°-24°C)
SPF+ 2.8 HFO VF (Very Fast)	40°-55°F (4.5°-13°C)

The information herein should not be considered all-inclusive and should always be accompanied by a review of the MuleHide specifications and guidelines and good application practices.

This information herein is based upon data and knowledge considered to be true and accurate at the time of printing and is provided for the reader's consideration, investigation and verification. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. ("MuleHide"). MuleHide does not warrant any results to be obtained. Statements concerning possible use of MuleHide products are made without knowledge of your particular roof and such an application may not be fit for your particular purpose. MULEHIDE DISCLAIMS ALL WARRANTIES, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, except written warranties attached to MuleHide products and written warranties signed by an officer of MuleHide.

Visit the MuleHide website at www.mulehide.com prior to any installation for updated technical specifications and details. MuleHide is a U.S. registered trademark. All rights reserved. REV 4 12/24