

# Torch Base SA

Self-Adhered SBS Membrane Base Sheet



The Right Choice for Low-Slope Roofing Products

800-786-1492 • mulehide.com

Rugged • Time-Tested • Weather-Tested

## TORCH BASE SA

A self-adhered, fiberglass reinforced, modified bitumen membrane manufactured to meet the toughest industry and code requirements. Torch Base SA is manufactured using Adeso® dual-compound technology, where the membrane consists of Styrene Butadiene Styrene (SBS) modified asphalt compound on top and a pressure sensitive adhesive compound on the bottom. The adhesive is covered with a split release liner. Torch Base SA is finished with a polyolefin film with printed lay lines on the top surface.

### BASIC USES

Torch Base SA membrane is specially designed for applications where the use of hot asphalt, cold process adhesive, or a propane torch is undesirable. Applications include new roofing, recover (retrofit) and BUR repairs. Torch Base SA can be used as a waterproofing base sheet applied to approved roof decks or substrates. Do not apply to shingles, shakes or other residential roofing material. See the Mule-Hide Self-Adhered Modified Bitumen Application Guidelines for complete specifications and details.

### PRODUCT BENEFITS

- Pre-applied adhesive on the back of the sheet.
- Durable - high performance reinforcement mat.
- No hot asphalt, fumes or flames required for installation.
- Excellent long term adhesion to multiple substrates and to base plies.
- Offers low-temp flexibility, puncture and tear resistance.
- Superior flexibility and dimensional stability



TORCH BASE SA					
Product Code	Description	Thickness	Coverage	Weight	Carton
06MHATBSA	65' 8" x 39-3/8" (20m x 1m)	1.65mm (65mils)	200 ft <sup>2</sup>	86 lbs.	2 Sq. Roll



D4601 TYPE II,  
D1970

Various code approvals are available including:  
Factory Mutual, Underwriters Laboratories,  
Miami-Dade, Florida Product Approval, ICC-ESR and  
Texas Department of Insurance. Contact Mule-Hide  
Technical Department for specific ratings.

The information herein should not be considered all-inclusive and should always be accompanied by a review of the Mule-Hide specifications and guidelines and good application practices.

This information herein is based upon data and knowledge considered to be true and accurate at the time of printing and is provided for the reader's consideration, investigation and verification. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Mule-Hide Products Co., Inc. does not warrant any results to be obtained. Statements concerning possible use of Mule-Hide products are made without knowledge of your particular roof and such an application may not be fit for your particular purpose. MULE-HIDE DISCLAIMS ALL WARRANTIES, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, except written warranties attached to Mule-Hide products and written warranties signed by an officer of Mule-Hide.

Visit the Mule-Hide website at [www.mulehide.com](http://www.mulehide.com) prior to any installation for updated technical specifications and details. Mule-Hide is a U.S. registered trademark. All rights reserved.  
REV 0 3/22