

- Roofing Products & Accessories -



Self-adhered, dual reinforced waterproofing underlayment for tile roofing systems

Now with 360 Days of UV Exposure*

FEATURES & BENEFITS

- ADESO® Self-Adhered Dual-Compound Technology
- Split-release film/paper for ease of installation
- Nail sealability
- Patented SEALLap® factory-applied adhesive treatment along the side lap
- Surfaces engineered for superior slip-resistance and long-term performance
- Increased labor efficiency and roof dry-in speed
- Safe no flames, fumes or odors

Approvals	Shur-Gard TU Force HT	Competitor A	Competitor B
FBC Non-HVHZ	V	V	V
FBC HVHZ	V		~
Miami-Dade NOA	V		~
FRSA/TRI 09-18	V	~	~
ASTM D1970	V	V	V
TAS 103	V		~
UV Exposure	360 Days*	360 Days	180 Days

All Mule-Hide Products Co., Inc. underlayments meet or exceed industry code approvals. Shur-Gard TU Force HT features up to 12-month exposure (mechanically attached roof cover), up to 6-month exposure (adhesive-set roof covering). Refer to local codes, listings or requirement of the AHJ. Codes supersede Mule-Hide requirements and recommendations. Florida Building Code Approval for exposure beyond 6-months is pending.





Code Approvals/Compliance:













^{*}Approved as part of a multi-ply system with mechanically fastened prepared roof coverings only. Tile applications only.