



SILICONE PROJECTS

100% SILICONE ROOF COATING SYSTEM

STEP 1: Clean the roof surface with **115 Cleaner** and lightly pressure wash

STEP 2: Identify if **Primer** is needed; adhesion test required for single-ply and metal substrates

STEP 3: Prep seams, joints, laps, protrusions & fasteners with **100% Silicone Sealant** or **Seal-Fast® Liqui-Flash**.

STEP 4: Apply **100% Silicone Roof Coating** with roller or sprayer at specified rate

SILICONE CLEANER

- 115 Cleaner (16MHA1155)



SILICONE PRIMER

- Multibase SB (16MHMBSB5)
- A-125 Metal Roof Primer (16MHA1255)
- Si TPO Primer (16MHSITPR5)



SILICONE SEALANT

- Silicone Sealant (16MHMBSB5)
Only up to 10 year spec.
- Seal-Fast® Liqui-Flash (16MHLFWH35)
Required for 15 and 20 year spec.



SILICONE COATING

- 100% Silicone Roof Coating (16MHSIRC5)



Colors available:



White



Black



Gray



Tan



Santa Fe Tan



Custom Color

The information herein should not be considered all-inclusive and should always be accompanied by a review of the MuleHide specifications and guidelines and good application practices. Statements concerning possible use of MuleHide products are made without knowledge of your particular roof and such an application may not be fit for your particular purpose. Visit the MuleHide website at www.mulehide.com prior to any installation for updated technical specifications and details.