





- 1** AT T-JOINT INTERSECTIONS BETWEEN ANY OF THE FOLLOWING, INSTALL A T-JOINT PATCH CENTERED OVER THE INTERSECTION:
- 60-MIL OR THICKER TPO REINFORCED OR SELF-ADHERING MEMBRANE
 - 115-MIL OR THICKER FLEECE BACK MEMBRANE
 - 135-MIL OR THICKER FLEECE BACK PLUS MEMBRANE

WARRANTY LENGTH	T-JOINT PATCH MATERIAL
20 YEAR	TPO FIELD CUT NON-REINFORCED FLASHING - APPROX 6"X6" W/ ROUNDED CORNERS
25/30 YEAR	PRE-FORMED T-JOINT PATCH

- 2** FASTENERS AND PLATES ARE NOT REQUIRED AND END LAPS.



T-JOINT INTERSECTIONS AT END LAP

APPLICABLE FIELD MEMBRANE (AND SYSTEMS)
TPO FLEECE BACK (MECHANICALLY ATTACHED)

MULEHIDE

TPO FB MECHANICALLY ATTACHED T-JOINT INTERSECTION

WHEN THE SYSTEM TYPE AND PROJECT DESIGN PERMIT, THIS DETAIL IS
ACCEPTABLE FOR : **MAXIMUM 20 YEAR WARRANTY**

DETAIL NO.:
TP-SM-A907

REVISION DATE: 8/24/2026