





REFER TO TERMINATION OR
METAL EDGE DETAILS



- 1 EHD FASTENERS WITH 2.4" SEAM PLATES ARE APPROVED FOR WOOD AND STEEL (18 - 22 GA.) SUBSTRATES. REFER TO SPECIFICATIONS FOR ACCEPTABLE PULLOUT VALUES, OR FOR OTHER FASTENERS AND COMPATIBLE SUBSTRATES.
- 2 NOTE THE FOLLOWING WHEN DETAIL EXISTS AT A PERIMETER PARAPET WALL:
 - ON MECHANICALLY ATTACHED SYSTEMS - FASTENER SPACING MUST NOT EXCEED THE SPACING SPECIFIED FOR PERIMETER SHEETS, WHICH MAY BE CLOSER THAN 12" O.C. BASED ON THE WARRANTY REQUIREMENTS. REFER TO SPECIFICATIONS.
 - FASTENER SPACING IS REQUIRED AT 6" O.C. WITH A WARRANTY EXCEEDING 90 MPH WIND SPEED COVERAGE OR FOR WARRANTIES GREATER THAN 20 YEARS.
- 3 MIN. 9" WIDE CUT STRIPS OF TPO SELF-ADHERING MEMBRANE MAY ALSO BE USED WITH THE TOP SIDE FACING UP.
- 4 ENSURE A 2" HANDROLLER IS USED FOR ADEQUATE PRESSURE/CONTACT OF MEMBRANE TO RUSS.

APPLICABLE FIELD MEMBRANE (AND SYSTEMS)
TPO SELF-ADHERING (ADHERED)

MULEHIDE

TPO SA WALL BASE ATTACHMENT W/ RUSS: "VERTICAL ATTACHMENT"

WHEN THE SYSTEM TYPE AND PROJECT DESIGN PERMIT, THIS DETAIL IS
ACCEPTABLE FOR : **MAXIMUM 30 YEAR WARRANTY**

DETAIL NO.:
TP-WF-C211

REVISION DATE: 8/24/2026