

---

**Section 1 - PRODUCT AND COMPANY IDENTIFICATION**

---

**Material Name**

Mule-Hide White Splice Adhesive

**Synonyms**

Contact Splicing Adhesive

**Chemical Family**

Contact Adhesive

**Product Use**

Contact Cement

**Restrictions on Use**

For industrial use only.

**Supplier Information:****Manufacturer Information:**

Carlisle SynTec  
1285 Ritner Highway  
Carlisle, PA 17013  
USA  
Phone: +1-800-479-6832  
Emergency Phone #: +1-800-424-9300 (CHEMTREC)

Mule-Hide Products Co., Inc  
1195 Prince Hall Dr.  
Beloit, WI 53511  
USA  
Phone: 800-786-1492

---

**Section 2 - HAZARDS IDENTIFICATION**

---

**Classification in accordance with paragraph (d) of 29 CFR 1910.1200.**

Flammable Liquids - Category 2

Aspiration Hazard - Category 1

Skin Corrosion/Irritation - Category 2

Serious Eye Damage/Eye Irritation - Category 2A

Skin Sensitization - Category 1A

Specific Target Organ Toxicity - Single Exposure - Category 1 ( central nervous system )

Specific Target Organ Toxicity - Single Exposure - Category 3

Specific Target Organ Toxicity - Repeated Exposure - Category 1 ( central nervous system, respiratory system )

**GHS Label Elements****Symbol(s)****Signal Word**

Danger

**Hazard Statement(s)**

Highly flammable liquid and vapor  
May be fatal if swallowed and enters airways  
Causes skin irritation  
Causes serious eye irritation  
May cause allergic skin reaction  
Causes damage to organs  
May cause respiratory irritation. May cause drowsiness or dizziness  
Causes damage to organs through prolonged or repeated exposure

**Precautionary Statement(s)****Prevention**

Keep container tightly closed  
Keep away from heat/sparks/open flame/hot surfaces - No smoking  
Ground/Bond container and receiving equipment  
Use explosion-proof electrical/ventilating/lighting equipment  
Take precautionary measures against static discharge  
Use only non-sparking tools  
Use only outdoors or in a well-ventilated area  
Wear protective gloves/protective clothing/eye protection/face protection  
Do not breathe dust/fume/gas/mist/vapours/spray  
Wash thoroughly after handling  
Contaminated work clothing must not be allowed out of the workplace  
Do not eat, drink or smoke when using this product

**Response**

In case of fire: Use appropriate media to extinguish  
If exposed: Call a POISON CENTER or doctor/physician  
IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing  
Call a POISON CENTER or doctor if you feel unwell  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If eye irritation persists: Get medical advice/attention  
IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower  
If skin irritation or rash occurs: Get medical advice/attention  
Take off contaminated clothing and wash before reuse  
IF SWALLOWED: Immediately call a POISON CENTER/doctor  
Do NOT induce vomiting  
Specific treatment (see label)

**Storage**

Store in a well-ventilated place. Keep container tightly closed  
Keep cool  
Store locked up

**Disposal**

Dispose of contents/container in accordance with local/regional/national/international regulations

**Other Hazards**

No additional information available.

---

**Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS**

---

CAS	Component Name	Percent
Mixture	Isophorone Diisocyanate	1-5
64742-89-8	Solvent naphtha, petroleum, light aliphatic	7-13
108-88-3	Toluene	30-60
13463-67-7	Titanium dioxide	0.1-1
Mixture	Silicon adsorbent mixture	0.5-1.5
112926-00-8	Silica, amorphous, precipitated and gel	1-5
1314-13-2	Zinc oxide	0.1-1
Trade Secret	Polyphenol antioxidant	0.1-1

---

**Section 4 - FIRST AID MEASURES**

---

**Description of Necessary Measures**

If exposed or concerned: Call a POISON CENTER or doctor/physician.

**Inhalation**

Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor if you feel unwell.

**Skin**

Remove/take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs, seek medical advice/attention.

**Eyes**

Rinse cautiously with water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists, get medical advice/attention.

**Ingestion**

Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.

**Indication of any immediate medical attention and special treatment needed**

Treat symptomatically and supportively.

**Most Important Symptoms/Effects**

**Acute**

May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause allergic skin reaction. Causes damage to central nervous system. May cause respiratory irritation. May cause drowsiness or dizziness.

**Delayed**

May cause damage to organs through prolonged or repeated exposure: central nervous system, respiratory system.

**Note to Physicians**

Contains toluene, heptane.

---

**Section 5 - FIRE FIGHTING MEASURES**

---

**Extinguishing Media****Suitable Extinguishing Media**

Dry chemical, foam or carbon dioxide. Water may be ineffective.

**Unsuitable Extinguishing Media**

Do not use high-pressure water streams.

**Special Hazards Arising from the Chemical**

Highly flammable liquid and vapor. May explode if heated in closed container. Vapors are heavier than air and may travel a considerable distance to a source of ignition and flashback.

**Hazardous Combustion Products**

Oxides of carbon, oxides of nitrogen

**Advice for firefighters**

Empty containers may contain product residue. Vapors can ignite explosively.

**Fire Fighting Measures**

Eliminate all ignition sources if safe to do so. Ground/Bond container and receiving equipment. Take precautionary measures against static discharge. Use only non-sparking tools. Avoid inhalation of material or combustion by-products.

**Special Protective Equipment and Precautions for Firefighters**

Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

---

**Section 6 - ACCIDENTAL RELEASE MEASURES**

---

**Personal Precautions, Protective Equipment and Emergency Procedures**

Wear personal protective clothing and equipment, see Section 8.

**Methods and Materials for Containment and Cleaning Up**

Remove all sources of ignition. Avoid breathing vapors. Ventilate affected area. Absorb with earth, sand or other non-combustible material and transfer to container. Dike for later disposal. Dispose in accordance with all applicable regulations.

**Environmental Precautions**

Avoid release to the environment.

## Section 7 - HANDLING AND STORAGE

**Precautions for Safe Handling**

This product contains titanium dioxide, which is a known carcinogen: Do not grind or sand. Keep container tightly closed. Keep away from heat, sparks, open flame, and hot surfaces - No smoking. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take precautionary measures against static discharge. Use only non-sparking tools. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Do not breathe dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. **KEEP OUT OF REACH OF CHILDREN.**

**Conditions for Safe Storage, Including any Incompatibilities**

Store in a well-ventilated place. Keep container tightly closed

Keep cool

Store locked up

Keep away from heat and ignition sources. Keep away from incompatible materials. Do not cut, puncture, or weld on or near this container.

**Incompatible Materials**

Acids, bases, strong oxidizing agents

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

**Component Exposure Limits**

<b>Toluene</b>	108-88-3	
ACGIH:	20 ppm TWA	
NIOSH:	100 ppm TWA; 375 mg/m <sup>3</sup> TWA	150 ppm STEL; 560 mg/m <sup>3</sup> STEL
	500 ppm IDLH	
Europe:	50 ppm TWA; 192 mg/m <sup>3</sup> TWA	100 ppm STEL; 384 mg/m <sup>3</sup> STEL
	Possibility of significant uptake through the skin	
OSHA (US):	200 ppm TWA	300 ppm Ceiling
Mexico:	50 ppm TWA LMPE-PPT; 188 mg/m <sup>3</sup> TWA LMPE-PPT	
	Skin - potential for cutaneous absorption	
<b>Titanium dioxide</b>	13463-67-7	

## Safety Data Sheet

**Material Name: Mule-Hide White Splice Adhesive**
**SDS 10-3310**

ACGIH:	10 mg/m <sup>3</sup> TWA	
NIOSH:	5000 mg/m <sup>3</sup> IDLH	
OSHA (US):	15 mg/m <sup>3</sup> TWA total dust	
Mexico:	10 mg/m <sup>3</sup> TWA LMPE-PPT as Ti	20 mg/m <sup>3</sup> STEL [LMPE-CT] as Ti
<b>Silicon adsorbent mixture</b>	Mixture	
NIOSH:	6 mg/m <sup>3</sup> TWA	3000 mg/m <sup>3</sup> IDLH
OSHA (US):	20 mppcf TWA; ((80)/(% SiO <sub>2</sub> )) mg/m <sup>3</sup> TWA	
<b>Silica, amorphous, precipitated and gel</b>	112926-00-8	
OSHA (US):	20 mppcf TWA; ((80)/(% SiO <sub>2</sub> )) mg/m <sup>3</sup> TWA	
Mexico:	10 mg/m <sup>3</sup> TWA LMPE-PPT	
<b>Zinc oxide</b>	1314-13-2	
ACGIH:	2 mg/m <sup>3</sup> TWA respirable fraction	10 mg/m <sup>3</sup> STEL respirable fraction
NIOSH:	5 mg/m <sup>3</sup> TWA dust and fume	10 mg/m <sup>3</sup> STEL fume
	15 mg/m <sup>3</sup> Ceiling dust	500 mg/m <sup>3</sup> IDLH
OSHA (US):	5 mg/m <sup>3</sup> TWA fume; 15 mg/m <sup>3</sup> TWA total dust; 5 mg/m <sup>3</sup> TWA respirable fraction	
Mexico:	5 mg/m <sup>3</sup> TWA LMPE-PPT fume; 10 mg/m <sup>3</sup> TWA LMPE-PPT dust	
	10 mg/m <sup>3</sup> STEL [LMPE-CT] fume	

**Biological limit value**

There are no biological limit values for any of this product's components.

**Engineering Controls**

Provide local exhaust ventilation system. Ensure compliance with applicable exposure limits.

**Individual Protection Measures, such as Personal Protective Equipment**
**Eye/face protection**

Wear safety glasses with side shields. Provide an emergency eye wash fountain and quick drench shower in the immediate work area.

**Skin Protection**

Wear work clothes with long sleeves. Wear chemical resistant clothing and rubber boots when potential for contact with the material exists. Recommended material: protective skin cream.

**Respiratory Protection**

A NIOSH approved air-purifying respirator with an appropriate cartridge or canister may be appropriate under certain circumstances where airborne concentrations are expected to exceed exposure limits.

**Glove Recommendations**

Wear appropriate chemical resistant gloves.

---

**Section 9 - PHYSICAL AND CHEMICAL PROPERTIES**

---

<b>Appearance</b>	white liquid	<b>Physical State</b>	liquid
<b>Odor</b>	hydrocarbon odor	<b>Color</b>	white
<b>Odor Threshold</b>	Not available	<b>pH</b>	Not available
<b>Melting Point</b>	-95 °C (-139 °F)	<b>Boiling Point</b>	90 - 111 °C (194-231 °F)
<b>Freezing point</b>	Not available	<b>Evaporation Rate</b>	2.6
<b>Boiling Point Range</b>	Not available	<b>Flammability (solid, gas)</b>	Not available
<b>Autoignition</b>	230 °C (475 °F)	<b>Flash Point</b>	-7.2 °C (19 °F)
<b>Lower Explosive Limit</b>	1 %	<b>Decomposition</b>	Not available
<b>Upper Explosive Limit</b>	7 %	<b>Vapor Pressure</b>	28.2 mmHg
<b>Vapor Density (air=1)</b>	3.3	<b>Specific Gravity (water=1)</b>	Not available
<b>Water Solubility</b>	Negligible	<b>Partition coefficient: n-octanol/water</b>	Not available
<b>Viscosity</b>	3800 cps	<b>Solubility (Other)</b>	Not available
<b>Density</b>	0.89 (relative)	<b>VOC</b>	637 g/L

**Other Information**

No additional information available.

---

**Section 10 - STABILITY AND REACTIVITY**

---

**Reactivity**

No reactivity hazard is expected.

**Chemical Stability**

Stable under normal conditions of use.

**Possibility of Hazardous Reactions**

Hazardous polymerization will not occur.

**Conditions to Avoid**

Avoid heat, flames, sparks and other sources of ignition. Avoid contact with incompatible materials.

**Incompatible Materials**

Acids, bases, strong oxidizing agents

**Hazardous decomposition products**

Oxides of carbon, oxides of nitrogen

---

**Section 11 - TOXICOLOGICAL INFORMATION**

---

**Information on Likely Routes of Exposure****Inhalation**

May cause respiratory irritation. May cause drowsiness or dizziness.

**Skin Contact**

Causes skin irritation. May cause allergic skin reaction.

**Eye Contact**

Causes serious eye irritation.

**Ingestion**

May be fatal if swallowed and enters airways. May cause gastrointestinal irritation.

**Acute and Chronic Toxicity****Component Analysis - LD50/LC50**

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Isophorone Diisocyanate (Mixture)

Oral LD50 Rat >20000 mg/kg

Inhalation LC50 Rat 5 mg/L 4 hr

Solvent naphtha, petroleum, light aliphatic (64742-89-8)

Oral LD50 Rat >2000 mg/kg

Dermal LD50 Rat >2000 mg/kg

Inhalation LC50 Rat >5000 ppm 1 hr

Toluene (108-88-3)

Oral LD50 >7000 mg/kg

Dermal LD50 12 - 14 g/kg

Inhalation LC50 30 - 35 mg/L

Titanium dioxide (13463-67-7)

Oral LD50 Rat >5000 mg/kg

Inhalation LC50 >6.82 mg/L 4 hr

Silicon adsorbent mixture (Mixture)



**Material Name: Mule-Hide White Splice Adhesive**

**SDS 10-3310**

Oral LD50 Rat >32000 mg/kg  
 Dermal LD50 Rabbit >2000 mg/kg  
 Inhalation LC50 Rat >2.2 mg/L 1 h

Zinc oxide (1314-13-2)

Oral LD50 Rat >15000 mg/kg  
 Inhalation LC50 Rat >5.7 mg/L

Polyphenol antioxidant (Trade Secret)

Oral LD50 Rat >5000 mg/kg  
 Dermal LD50 Rabbit >5000 mg/kg  
 Inhalation LC50 Rat >165 mg/L 1 h

Thermoplastic elastomer (Trade Secret)

Oral LD50 >2000 mg/kg  
 Dermal LD50 >2000 mg/kg

### Immediate Effects

May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause allergic skin reaction. Causes damage to central nervous system. May cause respiratory irritation. May cause drowsiness or dizziness.

### Delayed Effects

Causes damage to organs through prolonged or repeated exposure: central nervous system, respiratory system.

### Irritation/Corrosivity Data

Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation.

### Respiratory Sensitization

No data available.

### Dermal Sensitization

May cause allergic skin reaction.

### Component Carcinogenicity

<b>Toluene</b>	108-88-3
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
IARC:	Monograph 71 [1999]; Monograph 47 [1989] (Group 3 (not classifiable))
<b>Titanium dioxide</b>	13463-67-7
ACGIH:	A4 - Not Classifiable as a Human Carcinogen
IARC:	Monograph 93 [2010]; Monograph 47 [1989] (Group 2B (possibly carcinogenic to humans))
DFG:	Category 3A (could be carcinogenic for man, inhalable fraction with the exception of ultra small particles)
OSHA:	Present

<b>Silicon adsorbent mixture</b>	Mixture
IARC:	Monograph 68 [1997]; Supplement 7 [1987] (Group 3 (not classifiable))
<b>Silica, amorphous, precipitated and gel</b>	112926-00-8
IARC:	Monograph 68 [1997] (Group 3 (not classifiable))

**Germ Cell Mutagenicity**

No data available.

**Tumorigenic Data**

No data available

**Reproductive Toxicity**

No data available.

**Specific Target Organ Toxicity - Single Exposure**

Central nervous system

**Specific Target Organ Toxicity - Repeated Exposure**

Respiratory system, central nervous system

**Aspiration hazard**

May be fatal if swallowed and enters airways.

**Medical Conditions Aggravated by Exposure**

No data available.

**Additional Data**

This product contains titanium dioxide, which is a known carcinogen. However, this component is bound by the polymer portion of the sealant. The only way this component would be released is through incineration. Therefore, this product is not considered a carcinogen.

### Section 12 - ECOLOGICAL INFORMATION

**Ecotoxicity**

Avoid release to the environment.

**Component Analysis - Aquatic Toxicity**

<b>Solvent naphtha, petroleum, light aliphatic</b>	64742-89-8
Algae:	EC50 72 h Pseudokirchneriella subcapitata 4700 mg/L IUCLID

<b>Toluene</b>	108-88-3
Fish:	LC50 96 h Pimephales promelas 15.22 - 19.05 mg/L [flow-through] (1 day old); LC50 96 h Pimephales promelas 12.6 mg/L [static]; LC50 96 h Oncorhynchus mykiss 5.89 - 7.81 mg/L [flow-through]; LC50 96 h Oncorhynchus mykiss 14.1 - 17.16 mg/L [static]; LC50 96 h Oncorhynchus mykiss 5.8 mg/L [semi-static]; LC50 96 h Lepomis macrochirus 11 - 15 mg/L [static]; LC50 96 h Oryzias latipes 54 mg/L [static]; LC50 96 h Poecilia reticulata 28.2 mg/L [semi-static]; LC50 96 h Poecilia reticulata 50.87 - 70.34 mg/L [static]
Algae:	EC50 96 h Pseudokirchneriella subcapitata >433 mg/L IUCLID; EC50 72 h Pseudokirchneriella subcapitata 12.5 mg/L [static] EPA
Invertebrate:	EC50 48 h Daphnia magna 5.46 - 9.83 mg/L [static] EPA; EC50 48 h Daphnia magna 11.5 mg/L IUCLID
<b>Silicon adsorbent mixture</b>	Mixture
Fish:	LC50 96 h Brachydanio rerio 5000 mg/L [static]
Algae:	EC50 72 h Pseudokirchneriella subcapitata 440 mg/L IUCLID
Invertebrate:	EC50 48 h Ceriodaphnia dubia 7600 mg/L IUCLID
<b>Polyphenol antioxidant</b>	Trade Secret
Fish:	LC50 96 h Oncorhynchus mykiss >0.2 mg/L [semi-static]
Algae:	EC50 72 h Pseudokirchneriella subcapitata >0.2 mg/L IUCLID
Invertebrate:	EC50 48 h Daphnia magna >0.2 mg/L IUCLID

**Persistence and Degradability**

No information available for the product.

**Bioaccumulative Potential**

No information available for the product.

**Mobility**

No information available for the product.

**Other Toxicity**

No additional information available.

---

### Section 13 - DISPOSAL CONSIDERATIONS

---



# Safety Data Sheet

Material Name: Mule-Hide White Splice Adhesive

SDS 10-3310

### Disposal Methods

Dispose of contents/container in accordance with local/regional/national/international regulations.

## Section 14 - TRANSPORT INFORMATION

### US DOT Information:

**Shipping Name:** Adhesives

**Hazard Class:** 3

**UN/NA #:** UN1133

**Packing Group:** II

**Required Label(s):** 3

**Additional information:** Special Provisions (172.102): 149, B52, IB2, T4, TP1, TP8

### IATA Information:

**UN#:** UN1133

### IMDG Information:

**UN#:** UN1133

### TDG Information:

**UN#:** UN1133

## Section 15 - REGULATORY INFORMATION

### U.S. Federal Regulations

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Toluene	108-88-3
SARA 313:	1 % de minimis concentration
CERCLA:	1000 lb final RQ; 454 kg final RQ

### SARA Section 311/312 (40 CFR 370 Subparts B and C)

**Acute Health:** Yes **Chronic Health:** Yes **Fire:** Yes **Pressure:** No **Reactivity:** No

### U.S. State Regulations

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA
Toluene	108-88-3	Yes	Yes	Yes	Yes	Yes
Titanium dioxide	13463-67-7	No	Yes	Yes	Yes	Yes
Silicon adsorbent mixture	Mixture	Yes	Yes	Yes	Yes	Yes

## Safety Data Sheet

**Material Name: Mule-Hide White Splice Adhesive**
**SDS 10-3310**

Silica, amorphous, precipitated and gel	112926-00-8	No	Yes	Yes	Yes	Yes
Zinc oxide	1314-13-2	Yes	Yes	Yes	Yes	Yes

**The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):**

WARNING! This product contains a chemical known to the state of California to cause cancer  
 WARNING! This product contains a chemical known to the state of California to cause reproductive/developmental effects

Toluene	108-88-3
Repro/Dev. Tox	developmental toxicity , 1/1/1991
Titanium dioxide	13463-67-7
Carc:	carcinogen , 9/2/2011 (airborne, unbound particles of respirable size)

**Canadian WHMIS Ingredient Disclosure List (IDL)**

Components of this material have been checked against the Canadian WHMIS Ingredients Disclosure List. The List is composed of chemicals which must be identified on MSDSs if they are included in products which meet WHMIS criteria specified in the Controlled Products Regulations and are present above the threshold limits listed on the IDL

Toluene	108-88-3
	1 %
Silicon adsorbent mixture	Mixture
	1 %
Zinc oxide	1314-13-2
	1 %

**Component Analysis - Inventory**

Isophorone Diisocyanate (Mixture)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	No

Solvent naphtha, petroleum, light aliphatic (64742-89-8)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	No	No	Yes	No	Yes	Yes	Yes

Toluene (108-88-3)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX

## Safety Data Sheet

**Material Name: Mule-Hide White Splice Adhesive**
**SDS 10-3310**

Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes
-----	-----	-----	-----	-----	-----	----	-----	----	-----	-----	-----

Titanium dioxide (13463-67-7)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Silicon adsorbent mixture (Mixture)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Silica, amorphous, precipitated and gel (112926-00-8)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
No	DSL	No	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Zinc oxide (1314-13-2)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	Yes

Polyphenol antioxidant (Trade Secret)

US	CA	EU	AU	PH	JP - ENCS	JP - ISHL	KR - KECI/KECL	KR - TCCA	CN	NZ	MX
Yes	DSL	EIN	Yes	Yes	Yes	No	Yes	No	Yes	Yes	No

### Section 16 - OTHER INFORMATION

**HMIS Rating**

Health: 2\* Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe \* = Chronic hazard

**NFPA Ratings**

Health: 2 Fire: 3 Reactivity: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe



## Safety Data Sheet

Material Name: Mule-Hide White Splice Adhesive

SDS 10-3310

### Summary of Changes

New SDS: May 22, 2015

### Key / Legend

ACGIH - American Conference of Governmental Industrial Hygienists; ADR - European Road Transport; AU - Australia; BOD - Biochemical Oxygen Demand; C - Celsius; CA - Canada; CAS - Chemical Abstracts Service; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CLP - Classification, Labelling, and Packaging; CN - China; CPR - Controlled Products Regulations; DFG - Deutsche Forschungsgemeinschaft; DOT - Department of Transportation; DSD - Dangerous Substance Directive; DSL - Domestic Substances List; EEC - European Economic Community; EINECS - European Inventory of Existing Commercial Chemical Substances; EPA - Environmental Protection Agency; EU - European Union; F - Fahrenheit; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; ICAO - International Civil Aviation Organization; IDL - Ingredient Disclosure List; IDLH - Immediately Dangerous to Life and Health; IMDG - International Maritime Dangerous Goods; JP - Japan; Kow - Octanol/water partition coefficient; KR - Korea; LEL - Lower Explosive Limit; LLV - Level Limit Value; LOLI - List Of Lists™ - ChemADVISOR's Regulatory Database; MAK - Maximum Concentration Value in the Workplace; MEL - Maximum Exposure Limits; NFPA - National Fire Protection Agency; NIOSH - National Institute for Occupational Safety and Health; NJTSR - New Jersey Trade Secret Registry; NTP - National Toxicology Program; NZ - New Zealand; OSHA - Occupational Safety and Health Administration; PH - Philippines; RCRA - Resource Conservation and Recovery Act; REACH- Registration, Evaluation, Authorisation, and restriction of Chemicals; RID - European Rail Transport; SARA - Superfund Amendments and Reauthorization Act; STEL - Short-term Exposure Limit; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act; TWA - Time Weighted Average; UEL - Upper Explosive Limit; US - United States.

### Other Information

#### Disclaimer:

The information contained herein is based upon data and information available to us, and reflects our best professional judgment. This product may be formulated in part with components purchased from other companies. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent, since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use