



Product Data Sheet

MULE-HIDE #420 MOD BIT ADHESIVE – BRUSH GRADE

PRODUCT DESCRIPTION

Mule-Hide #420 Mod Bit Adhesive is a select formulation for use as a cold-applied bonding agent for SBS modified bitumen base sheets and SBS modified bitumen cap sheets. Specially formulated for use with Mule-Hide SAMB membranes.

BASIC USES

- Used to install SBS modified bitumen base sheets and SBS modified cap sheets to approved substrates such as structural concrete roof decks, existing smooth surfaced asphalt built-up roofs, approved roof insulations, glass fiber base sheets, and other approved surfaces.
- Can be used as an adhesive for APP sand back membranes.
- Bonds gravel or mineral granules to built-up roof systems and modified cap sheets.
- Can also be used for conventional built-up roofing systems.
- DO NOT USE with PVC, TPO, EPDM or other single-ply membranes.
- DO NOT USE over or under expanded polystyrene insulation.
- DO NOT USE under any APP product with a burn-off film.
- DO NOT USE with organic saturated felts.



PHYSICAL PROPERTY INFORMATION*

Property	Value
Maximum VOC	250 G/l
Consistency	Medium bodied liquid
Weight	7.7 lbs. per gallon
Flash Point (T.C.C.)	107°F+
Viscosity, stormer	130 ± 10

* Data reported is based on available independent and in-house resources. Mule-Hide reserves the right to change or modify, at its discretion, and without prior written notice, any of the information, requirements, specifications or policies contained in this document.

PACKAGING

4.7 Gallon Pail (17.79 Liters)

BENEFITS & SUPPLEMENTAL STATEMENTS

- Adheres to substrate and provides superior lap strength
- Flexible with cohesive properties
- Eliminates need for kettles and torches.
- Excellent 24 hour strength, fully cured after 30 days
- Non-destructive to conventional asphalt based roofing membranes.
- 100% recycled cellulose fibers

CODE APPROVALS/COMPLIANCE

- Miami Dade County Approved
- Meets or exceeds requirements of ASTM D3019

Product Data Sheet

MULE-HIDE #420 MOD BIT ADHESIVE – BRUSH GRADE

COVERAGE RATES AND SPRAY TIP SIZES

- Approximately 1 – 1.5 gallons per 100 sq. ft. when applied to a smooth surface
(All values are approximate and may vary with ambient temperature and job conditions)

INSTALLATION TEMPERATURE

- Apply only when ambient temperatures are 45°F and rising. Cold weather could result in uneven application and improper curing of product. Cold weather will cause product to stiffen making application more difficult.
- Store product at room temperature for minimum 24 hours prior to application.
- Do not heat container or attempt to thin this product.
- Not recommended for application on substrates that exceed 140°F.

INSTALLATION INSTRUCTIONS

Surface Preparation:

- All surfaces to receive coating must be clean, dry and free from any foreign matter such as oil, grease, dirt or any debris that could inhibit the bonding capabilities of the roof cement. Priming is recommended when adhering to questionable conditions.
- Blisters, buckles and raised edges should be cut out for a smooth surface.
- Check all flashing, edges, drains, valleys and vents and repair as needed.
- On gravel roofs, remove gravel before making repair.
- Do not use on wet or damp surfaces, directly over wood or surfaces previously covered with coal tar based products.

Installation Method:

- Unroll modified bitumen and base sheet rolls and allow them to lay flat prior to installation.
- Stir product well prior to application.
- Product may be installed by high pressure spray, notched squeegee, or brush application methods.
- After Adhesive Application: Install membrane within 15 minutes of adhesive application. Roll all side and end laps. Ensure that a sufficient amount of adhesive has been applied so that a bead of adhesive is visible at all lap edges after rolling.
- Two Layer Application: Install SBS base membrane in adhesive. Wait three to seven hours to allow base layer adhesive to set before installing the SBS cap membrane. Install SBS cap membrane and adhesive in similar fashion as SBS base membrane.
- Slope Restrictions: The adhesive may be used on slopes up to approximately 1 ½" per foot without back-nailing. Slopes greater than 1 ½" in per foot will require that the membrane be back-nailed.

PRECAUTIONS

COMBUSTIBLE LIQUID AND VAPOR

- Contains petroleum distillate. Harmful or fatal if swallowed. Close container after each use. **DO NOT TAKE INTERNALLY!** Vapor harmful. May affect the brain or central nervous system causing dizziness, headache, or nausea. Causes nose and throat irritation. Causes eye irritation. Causes skin irritation. Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Keep away from heat and open flame.
- Use only with adequate ventilation. **CLOSE AIR INTAKES** on roof until solvents dissipate. Do not breathe vapors. If you experience eye watering, headache, or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use.
- **California Proposition 65 Warning:** This product may contain chemicals known to the State of California to cause cancer, birth defects and/or reproductive harm.

Product Data Sheet

MULE-HIDE #420 MOD BIT ADHESIVE – BRUSH GRADE

PRECAUTIONS (continued)

Personal Protection – Irritation may result from prolonged or repeated contact with skin. Wear chemical resistant gloves, protective goggles and protective clothing, if needed.

Eye Contact – Rinse immediately with clean water for 15 minutes and see medical advice.

Waste Disposal – Empty containers must be disposed of in accordance with local, state, and federal regulations.

For Professional Use Only – Keep out of the reach of children.

For Exterior Use Only - Refer to material safety data sheet (MSDS) for specific data and handling.

CLEAN UP

- Clean tools with mineral spirits or paint thinner.

STORAGE & HANDLING

- Product shelf life is 18 months from date of manufacture when properly stored.
- Store container at room temperature for minimum 24 hours prior to use.
- Do not allow product to freeze. Discard if product becomes frozen.
- Do not store at temperatures greater than 120°F.
- Observe normal safeguards for storing and handling of product prior to and during use.
- Keep containers tightly covered when not in use.

PROTECTION & SAFETY

Mule-Hide maintains Safety Data Sheets on all of its non-exempt products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

ADDITIONAL INFORMATION

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at www.mulehide.com for the latest information, changes and updates or contact Mule-Hide Products Company at 800-786-1492.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.