



# Product Data Sheet

## EPDM CURB WRAP (BLACK AND WHITE)

### PRODUCT DESCRIPTION

Black Curb Wrap and White Curb Wrap provide an efficient means to flash a curb with EPDM materials. Curb Wrap is pre-cut to a 20" width and has 6" In-Seam Tape pre-applied. Production time can be substantially reduced with this labor saving product.

### BASIC USES

Black Curb Wrap and White Curb Wrap are used to efficiently flash roof curbs.

### SPECIFICATIONS

Typical Properties*	
Base:	Membrane – EPDM Adhesive – Synthetic Polymers
Thickness:	Membrane 60-mil (1.52 mm)
Size:	20" x 50' (508 mm by 15.2 m)
Packaging:	50 lf / carton (15.2 m) – 1 roll per carton
Weight:	30 lbs (13.6 Kg)
Shelf Life:	1 year when stored between 60°F and 80°F (15°C and 26°C)
*Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.	



### BENEFITS & SUPPLEMENTAL STATEMENTS

- Provides substantial labor savings for flashing curbs and walls
- Supplied in 20" x 50' rolls of cured 60-mil EPDM flashing
- 6" In-Seam Tape is pre-applied to Curb Wrap
- Cleaner appearance and stronger seams

### INSTALLATION INSTRUCTIONS

1. Install deck membrane and attach to base of curb as per Mule-Hide standard details.
2. Cut a strip of Curb Wrap long enough to wrap entire curb, plus a minimum of 3". (A 2' x 2' curb would require a minimum 8'-3" length of Curb Wrap)
3. Trim width of Curb Wrap as required. Tape side of Curb Wrap is to extend onto field membrane 6" to allow for a proper seam (in all cases In-Seam Tape must extend a minimum of 3" beyond outer edge of seam plates (if used)). Allow top edge of Curb Wrap to extend a minimum of 2" over the top of the curb. (Width = curb height + 8")
4. Place Curb Wrap on a flat surface with the tape side facing upwards. Do not remove release liner from In-Seam Tape.
5. Apply Bonding Adhesive to the curb and to the un-taped portion of the Curb Wrap.
6. While the bonding adhesive is drying, clean membrane surface with weathered membrane cleaner and apply Tape Primer to the seam area on the field membrane.
7. After adhesive has properly flashed off, bond the Curb Wrap to the roof curb. Wrap entire curb with the In-Seam Tape portion folded upwards with the release liner still in place. Care should be taken so as to not stretch the Curb Wrap.
8. To complete the seam between the Curb Wrap and field membrane, cut the Curb Wrap at each corner, allowing the taped portion of the Curb Wrap to fall in place. Round all cut corners. Press the Curb Wrap into the angle change as tightly as possible without stretching the material.

# Product Data Sheet

## EPDM CURB WRAP (BLACK AND WHITE)

---

### **INSTALLATION INSTRUCTIONS (continued)**

9. With the In-Seam Tape laying flat on the primed membrane surface, remove the release liner by pulling it out from underneath the Curb Wrap while simultaneously pressing the In-Seam Tape onto the primed membrane surface using firm even hand pressure. Work across the seam towards the outer seam edge. Immediately roll the seam with a 2" wide (50 mm) roller, using positive pressure.
10. Broom the mated Curb Wrap over the curb to ensure proper mating of the bonding adhesive.
11. Flashing the vertical seam in the Curb Wrap as per Mule-Hide detail MHE-111.
12. Flash the corners of the roof curb with Mule-Hide detail MHE-MHE-183.

Review Mule-Hide Specifications and details for additional application instructions.

### **PRECAUTIONS**

- Avoid prolonged contact with skin. In case of contact with skin, thoroughly wash affected area with soap and water.
- Prolonged jobsite storage temperatures in excess of 90°F (32°C) will shorten product shelf life.
- In warm, sunny weather, keep Curb Wrap in original box in a shaded area until ready to use.
- Storage and use of Curb Wrap at temperatures below 40°F (4°C) will result in a loss of tape tack and, in extreme cases, will result in no bond to the substrate. Overnight storage must be available to keep the temperature of the Curb Wrap at a minimum of 60°F (15°C). Hot boxes for jobsite storage must be provided to maintain a minimum tape temperature of 40°F (4°C).
- Curb Wrap must be stored in a dry area.
- Due to solvent flash-off, condensation may occur on freshly applied primer when the ambient temperature is near the dew point. If condensation develops, the application of primer must be discontinued as proper adhesion will not be achieved.
- Allow the primer surface to dry and apply a thin freshener coat of primer to the previously coated surface and apply Uncured Flashing Tape when conditions allow.
- Do not allow waste products (petroleum, grease, oil, solvents, vegetable or mineral oil, animal fats, etc.) or direct steam venting to come in contact with the Curb Wrap.
- KEEP OUT OF REACH OF CHILDREN

### **PROTECTION & SAFETY**

Mule-Hide maintains Safety Data Sheets on all of its non-exempt products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

### **ADDITIONAL INFORMATION**

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at [www.mulehide.com](http://www.mulehide.com) for the latest information, changes and updates or contact Mule-Hide Products Company at 800-786-1492.

### **DISCLAIMER**

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.