



Product Data Sheet

MULE-HIDE SEAL-FAST[®] TAPE PLUS

PRODUCT DESCRIPTION

Mule-Hide Seal-Fast[®] Tape Plus is a non-butyl synthetic rubber and resin adhesive tape, which remains flexible even in cold temperatures. The polyvinyl facer on the exposed side of the tape makes Seal-Fast[®] Tape Plus UV resistant and is available in Black and White. Seal-Fast[®] Tape Plus was designed specifically for granulated roofs and surfaces that require a deeper seal.



BASIC USES

Seal-Fast[®] Tape Plus may be used on a wide variety of surfaces including difficult roof materials such as : EPDM, TPO, most PVC, CSPE/Hypalon, CPE, SBS, APP modified, asphalt BURs, coal tar BURs, all metal roofs, tiles, shingle, aluminum, galvanized steel, gypsum board, wood, polyethylene, propylene, polystyrene, fiberglass, brick, concrete, masonry, OSB, etc.. This product may be used to repair gutters, chimney flashings, and metal roofs on mobile homes and transport vehicles. Seal-Fast[®] Tape Plus makes a permanent watertight seal. Can be installed in temperatures down to -20°F (with our Seal-Fast[®] Primer).

TYPICAL PHYSICAL PROPERTIES

Typical Physical Properties*	
Colors	White and Black
Total Thickness	65 mils (± 2 mils)
Adhesion	20 lbs + / inch width
Low temperature flexibility	½" radius at -30°F
Application temperature	>150°F to -20°F with optional primer
Temperature range	-70°F to >200°F
Pliability	No cracks
Water vapor – ASTM E96B	.005 grams / 100 sq. in. / 24 hrs / 100°F
Permeance	.001 perms maximum
Elongation	>700% ± 100
Tensile break	4500 psi ± 500 psi
Shelf life	Up to 5 years
*Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification range for any particular property of this product.	

COLORS

Available in Black and White

PACKAGING

Packaged in cartons

Size	Rolls / Carton	Weight / Carton	Colors
4" x 25'	6	24	White - Black
6" x 25'	4	24	White - Black
24" x 50'	1	24	White-Black-Gray

Product Data Sheet

MULE-HIDE SEAL-FAST[®] TAPE PLUS

BENEFITS

- Adheres to most surfaces
- Easily cut and formed
- Extra thick to accommodate granulated surfaces

INSTALLATION INSTRUCTIONS

SURFACE PREPARATION

1. Surface must be clean and dry, free of loose rust and scale, dust, talc and dirt.
2. Oil, grease and other contaminants must be removed with a Seal-Fast Cleaner or suitable solvent/cleaner.
3. For older plastic roofs, score surface with sand cloth and wipe away dust.

APPLICATION

1. Install Seal-Fast[®] Tape Plus over repair area, remove plastic liner gradually to prevent contamination of adhesive prior to application.
2. Rub or roll with pressure (preferably with a steel roller) to activate the bonding process.
3. Seal-Fast[®] Tape Plus may be applied to clean, dry surfaces from 150°F to -20°F.
4. For low temperature application (below 40°F down to -20°F) treat surface with Seal-Fast[®] Primer prior to application and maintain tape at room temperature (+60°F) prior to application..

STORAGE & HANDLING

Store Seal-Fast[®] Tape Plus in a cool, shaded area and cover with a light-colored, breathable, waterproof tarp.

PROTECTION & SAFETY

Mule-Hide maintains Safety Data Sheets on all of its products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

ADDITIONAL INFORMATION

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at www.mulehide.com for the latest information, changes and updates or contact Mule-Hide Products Company at 800-786-1492.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.