



Product Data Sheet

115 CLEANER

DESCRIPTION

115 CLEANER by Mule-Hide is a ready-to-use, environmentally friendly cleaner that is excellent at removing dirt, oil, and grease from a variety of surfaces.

Revision Date: Oct 2018

BASIC USES

115 CLEANER is used as a general purpose cleaner prior to the coating of approved surfaces with Mule-Hide Coatings Systems. Power washing with 115 CLEANER effectively removes existing oil, dirt, or grease that would adversely affect the bonding of new coatings, and prepares those surfaces for the new primer / coating.



PACKAGING

Packaging is standard in 5 gallon pails and 50 gallon drums.

STORAGE & HANDLING

- One year shelf life with proper storage.
- All materials are to be stored at not less than 45°F.

APPLICATION

1. All loose existing coatings, heavy rust, debris and fresh roof cement shall be removed prior to applying 115 cleaner.
2. Apply to surface with a garden type sprayer in sufficient quantity to wet out the surface for a minimum of 15 minutes without drying.
3. Apply at a minimum rate of 0.25 to 0.50 gallon per 100 square feet. Do not allow product to dry on roof surface.
4. Thoroughly power wash 115 CLEANER from surface until rinse water is clean. A final clean water rinse is recommended. This effectively removes existing oil, dirt, or grease that would adversely affect the bonding of acrylic coatings. Excessively soiled / greasy surfaces and rust or scale may require additional cleaning or scrubbing with a broom or brush.
5. EPDM substrates are properly cleaned when no black residue is present when swiping a finger or white cloth over the cleaned membrane.

PRECAUTIONS

Mule-Hide 115 CLEANER is a highly alkaline material. WEAR CHEMICAL SPLASH GOGGLES when applying 115 CLEANER. As with all chemicals, use caution and good industrial hygiene when handling and disposing of empty 115 CLEANER containers and ensure proper drainage for 115 CLEANER and rinse water run-off from the roof. The diluted 115 CLEANER rinse water can be safely discharged onto the ground surface. If in doubt, always contact the local authorities prior to discharging to the soil surface. Never discharge 115 CLEANER (nor the rinse water generated) directly into any open body of water. Refer to the 115 CLEANER SDS for additional information or contact Mule-Hide Technical Department, 800-786-1492.

CLEAN UP

Tools, hoses and equipment must be flushed and cleaned immediately with water.

Product Data Sheet

115 CLEANER

PROTECTION & SAFETY

Mule-Hide maintains Safety Data Sheets on all of its non-exempt products. Safety Data Sheets contain health and safety information for your development of appropriate product handling procedures to protect your employees and customers. Mule-Hide's Safety Data Sheets should be read and understood by all of your supervisory personnel and employees before using Mule-Hide products in your facilities.

ADDITIONAL INFORMATION

The information given on this PDS is subject to change without notice. Always check the Mule-Hide website at www.mulehide.com for the latest information, changes and updates or contact Mule-Hide Products Company at 800-786-1492.

DISCLAIMER

The statements provided concerning the material shown are intended as a guide for material usage and are believed to be true and accurate at the time of printing. No statement made by anyone may supersede this information, except when done in writing by Mule-Hide Products Co., Inc. Since the manner of use is beyond our control, Mule-Hide does not authorize anyone to make any warranty of merchantability or fitness for any particular purpose or any other warranty, guarantee or representation, expressed or implied, concerning this material. This product may be eligible for a Mule-Hide warranty, please check the Mule-Hide website at www.mulehide.com or contact Mule-Hide directly at 800-786-1492 for details. Buyer and user accept the product under these conditions and assume the risk of any failure, any injury person or property (including that of the user), loss or liability resulting from the handling, storage or use of the product whether or not it is handled, stored or used in accordance with the directions or specifications. Mule-Hide must be notified in writing of any claims and be given the opportunity to inspect the alleged failure before repairs are made.