

Technical Bulletin No. 1003

Use of Pactiv GreenGuard Roof Insulation In Mule-Hide Roofing Systems

Revised Sept-2016

Pactiv offers several roof insulations that may be used in Mule-Hide roofing systems. The Pactiv insulation is an extruded polystyrene product and care must be taken when using this material over coal tar pitch. The following is a brief summary of how these insulations may be utilized in a Mule-Hide system.

Sizes Insulation

PB6 Series Supplied as fanfold bundles, 4' x 50', 3/8" thick

PB38 Series and XPS Supplied as 4' x 8' sheets, 3/8" thick

Warranties - Pactiv insulations may be used for Standard 10, 15, or 20 year warranties when following our guidelines and Pactiv recommendations. (Not for use with Mule-Hide Premium Warranties)

Ballasted Systems

Membrane	Insulation	Installation
EPDM TPO	PB6, PB6FA or PB6W	Loosely laid in place*
	PB38, PB38FA or XPS	
PVC	NONE	Ballasting not permitted

^{*}Note: Insulation may be spot attached with adhesive to facilitate installation. Mechanical attachment of insulation is not allowed under a ballasted system.

Mechanically Attached Systems

Membrane	Insulation	Attachment (Min fasteners required) (4)
TPO ⁽¹⁾ (Light Colored)	PB6, PB6FA or PB6W	NON FM – 1 per 12 sq. ft.
		2 per 2' x 4' panel – FM pattern
	PB38, PB38FA or XPS	4 per 4' x 8' board – FM pattern
EPDM ⁽²⁾	PB6, PB6FA or PB6W	4 per 2' x 4' panel – FM pattern
(Dark Colored)	PB38, PB38FA or XPS	8 per 4' x 8' board – FM pattern
PVC ⁽³⁾	DDGEA or DDGW	NON FM – 1 per 12 sq. ft.
(Light Colored)	PB6FA or PB6W	2 per 2' x 4' panel – FM pattern

- (1) TPO (White, Tan, Gray)
- (2) Reinforced EPDM
- (3) PVC (White, Tan, Gray)
- (4) See fastening patterns attached to this Tech Bulletin.
- (5) Follow GreenGuard application instructions, available at www.green-guard.com

Any information given on this Technical Bulletin is subject to change without notice. Please visit our website at www.mulehide.com or contact Mule-Hide Products at (608) 365-3111 for questions or additional information.

MULE-HIDE PRODUCTS CO., INC.


1195 Prince Hall Dr. Beloit, WI 53511-5481

608-365-3111 • Fax: 608-365-7852 • www.mulehide.com

P.O. Box 1057 Beloit, WI 53512-1057

Technical Bulletin - No 1003

Fastening Patterns for Kingspan GreenGuard® Roofing Cover Board Used Under Light-Colored Roof Membranes



Fastening Patterns for Kingspan GreenGuard® Roofing Cover Board Used Under Dark-Colored Roof Membranes

