

PERIMETER EDGE METAL SHALL BE PRIMED WITH MULE-HIDE # 121 ASPHALT PRIMER OR FAST DRY PRIMER IN AEROSOL CAN MEETING ASTM D 41.

1" [25 mm] MIN. BELOW BLOCKING

MULE-HIDE MOD BIT SEALANT IF MEMBRANE IS NOT SET FLUSH TO THE EDGE OF THE METAL. IF SEALANT IS USED, COVER WITH LOOSE GRANULES. URETHANE SEALANT SUCH AS NP-1 MAY ALSO BE USED.

FASTENERS AT APPROX. 3" to 6" [75 to 150 mm] O.C., STAGGERED.

MULE-HIDE SA-SBS OR SA-APP CAP SHEET

MULE-HIDE SA BASE SHEET

APPROVED INSULATION OR COMBINATION OF APPROVED COVERBOARD/OVERLAY OVER INSULATION

ROOF DECK

WOOD NAILERS

EXTEND SA BASE SHEET

OPTIONAL: WOOD NAILER AND SHEET METAL CLOSURE

CONTINUOUS CLEAT FASTENED 12" O.C.

NOTES:

1. THIS DETAIL SHOULD BE USED ONLY WHERE THE DECK IS SUPPORTED BY THE OUTSIDE WALL.
2. REFER TO THE SHEET METAL SECTION OF THE NRCA ROOFING AND WATERPROOFING MANUAL FOR JOINERY AND SECUREMENT OPTIONS FOR SHEET METAL.

**MULE-HIDE
PRODUCTS CO.,INC.
2003**

EDGE METAL FLASHING - OPTION 1

SELF-ADHERING MOD BIT SYSTEMS

**DETAIL NO.:
MH-MB-EM1**